

The essential guide of Automation

helping you easily
select the right product

2008



Automation

Zelio

Relays and smart relays



Zelio relay range

Zelio Relay plug-in relays, Zelio Control control and measurement relays, Zelio Count counters, Zelio Time timing relays: These ranges offer *compactness* and *simplicity*.

Zelio Logic smart relays

Designed for management of simple automation systems comprising 10 to 40 I/O. Compact or modular, Zelio Logic offers *flexibility* and *simplicity*.

Modicon

Automation platforms



Modicon TSX Micro, ideal for compact machine builders. At the heart of the machine, TSX Micro offers *compactness*, *modularity* and *integration* benefits.

- CANopen machine bus connection
- Low cost Ethernet connection
- Doubling of memory capacity



New

Modicon M340, is designed for complex machine applications and infrastructures control. *Robust, powerful* and *compact* it meets your requirements for automation of industrial processes.

- CANopen machine and installation bus
- Ethernet TCP/IP network - Transparent Ready
- Modbus serial link and character mode



Modicon Premium, ideal for manufacturing and infrastructure applications. Outstanding *flexibility* for distributed architectures and *integration* of advanced automation system functions.

- New high performance processors
- CANopen machine bus connection, from entry level



New

Modicon Quantum, ideal for process applications. *High level of performance* for process control, process safety and architecture availability.

- New high performance processors
- Onboard Ethernet
- Memory expansion option using PCMCIA
- Safety new offer

Contents

Twido

Programmable controllers



Twido, ideal for simple installations and small machines: standard applications comprising 10 to 100 I/O (max. 252 I/O). Compact or modular, Twido offers *flexibility* and *simplicity*.

Relays

- **Zelio Relay** - Plug-in relays 2 to 3
- **Zelio analog** - Analog interface 4 to 5
- **Zelio Control** - Control and measurement relays 6 to 9
- **Zelio Count** - Counters 10 to 11
- **Zelio Time** - Timing relays 12 to 13
- **Zelio Logic** - Smart relays 14 to 15

Programmable controllers, Automation platforms


- **Twido** - Programmable controllers 16 to 19
- **Modicon TSX Micro** - Automation platforms 20 to 25
- **Modicon M340** - Automation platforms 26 to 33
- **Modicon Premium** - Automation platforms 34 to 41
- **Modicon Quantum** - Automation platforms 42 to 49
- **Unity** - Software 50 to 51
- **PL7, Concept, ProWORX 32** - Software 52 to 53

Modicon M340

The ideal solution for machine builders



Choosing Modicon M340 gives you the advantage of all the services of the Unity software offer, from the design through to the implementation of your application.





Type of relay	Interface relays RSB			Miniature relays RXM			
Contact characteristics							
Thermal current I _{th} in A (temperature ≤ 55°C)	8	12	16	12	10	6	3
Number of contacts	2 “C/O”	1 “C/O”	1 “C/O”	2 “C/O”	3 “C/O”	4 “C/O”	4 “C/O”
Contact material	AgNi	AgNi	AgNi	AgNi	AgNi	AgNi	AgAu
Switching voltage, min. / max.	5 / 250 VAC/DC			12 / 250 VAC/DC			
Switching capacity, min. / max. (mA / VA)	5 / 2000	5 / 3000	5 / 4000	10 / 3000	10 / 2500	10 / 1500	2 / 1500
Coil characteristics							
Average consumption, inrush,	0.75 VA / 0.45 W			1.2 VA / 0.9 W			
Permissible voltage variation	0.8/0.85...1.1 Un (50/ 60Hz or =)			0.8...1.1 Un (50 / 60Hz or =)			
References	(1)	(1)	(1)	(2)	(2)	(2)	
Coil supply voltage on DC	6 VDC	RSB2A080RD	RSB1A120RD	RSB1A160RD	—	—	—
	12 VDC	RSB2A080JD	RSB1A120JD	RSB1A160JD	RXM2AB2JD	RXM3AB2JD	RXM4AB2JD
	24 VDC	RSB2A080BD	RSB1A120BD	RSB1A160BD	RXM2AB2BD	RXM3AB2BD	RXM4AB2BD
	48 VDC	RSB2A080ED	RSB1A120ED	RSB1A160ED	RXM2AB2ED	RXM3AB2ED	RXM4AB2ED
	60 VDC	RSB2A080ND	RSB1A120ND	RSB1A160ND	—	—	—
	110 VDC	RSB2A080FD	RSB1A120FD	RSB1A160FD	RXM2AB2FD	RXM3AB2ED	RXM4AB2ED
Coil supply voltage on AC	24 VAC	RSB2A080B7	RSB1A120B7	RSB1A160B7	RXM2AB2B7	RXM3AB2B7	RXM4AB2B7
	48 VAC	RSB2A080E7	RSB1A120E7	RSB1A160E7	RXM2AB2E7	RXM3AB2E7	RXM4AB2E7
	120 VAC	RSB2A080F7	RSB1A120F7	RSB1A160F7	RXM2AB2F7	RXM3AB2F7	RXM4AB2F7
	220 VAC	RSB2A080M7	RSB1A120M7	RSB1A160M7	—	—	—
	230 VAC	RSB2A080P7	RSB1A120P7	RSB1A160P7	RXM2AB2P7	RXM3AB2P7	RXM4AB2P7
	240 VAC	RSB2A080U7	RSB1A120U7	RSB1A160U7	—	—	RXM4GB2U7

Sockets for relays

Type of socket			For interface relays RSB			For miniature relays RXM		
Mixed input/output type sockets with location for protection module								
			–	–	–	RXZE2M114(5)	–	RXZE2M114
			–	–	–	RXZE2M114M(5)	–	RXZE2M114M
Separate input/output type sockets with location for protection module								
			RSZE1S48M	RSZE1S35M	RSZE1S48M(3)	RXZE2S108M	RXZE2S111M	RXZE2S114M
Protection modules								
Diode	6...230 VDC	RZM040W			RXM040W			
	RC circuit	24...60 VAC	RZM041BN7			RXM041BN7		
Varistor	110...240 VAC	RZM041FU7			RXM041FU7			
	6...24 VDC or AC	RZM021RB (6)			RXM021RB			
	24...60 VDC or AC	RZM021BN (6)			RXM021BN			
	110...230 VDC or AC	RZM021FP (6)			RXM021FP			
	24 VDC or AC	–			–			
	240 VDC or AC	–			–			
Multifunction timer module	24...230 VDC or AC	–			–			
Accessories								
Plastic maintaining clamp			RSZR215			RXZR335		
Metal maintaining clamp			–			RXZ400		
Label for socket			RSZL300			RXZL420 (except RXZE2M114)		
Bus jumper	2 poles	–			RXZS2			
DIN rail adapter			–			RXZE2DA		
Panel mounting adapter			–			RXZE2FA		

(1) References for relays without socket, for relays with socket, add the letter **S** to the end of the selected reference. (Example: RSB2A080B7 becomes RSB2A080B7S).

(2) References for relays with LED, for relays without LED, replace the number 1 in the reference by **2**. (Example: RXM2AB2JD becomes RXM2AB1JD)

(3) To use RSB 1A160 ●● relay with socket, terminals must be interconnected

Universal and power relays



Universal relays RUM						Power relays RPM				RPF	
Cylindrics			Faston								
10	10	3	10	10		15	15	15	15	30 (4)	30 (4)
2 "C/O"	3 "C/O"	3 "C/O"	2 "C/O"	3 "C/O"		1 "C/O"	2 "C/O"	3 "C/O"	4 "C/O"	2 "N/O"	2 "C/O"
AgNi	AgNi	AgAu	AgNi	AgNi		AgNi	AgNi	AgNi	AgNi	AgSnO ₂	AgSnO ₂
12 / 250 VAC/DC						12 / 250 VAC/DC				12 / 250 VAC/DC	
10 / 2500	10 / 2500	3 / 750	10 / 2500	10 / 2500		100 / 3750	100 / 3750	100 / 3750	100 / 3750	100 / 7200	100 / 7200
2...3 VA / 1.4 W						0.9 VA / 0.7 W	1.2 VA / 0.9 W	1.5 VA / 1.7 W	1.5 VA / 2 W	4 VA / 1.7 W	
(2)	(2)	–	(2)	(2)		(2)	(2)	(2)	(2)	–	–
–	–	–	–	–		–	–	–	–	–	–
RUMC2AB2JD	RUMC3AB2JD	–	RUMF2AB2JD	RUMF3AB2JD		RPM12JD	RPM22JD	RPM32JD	RPM42JD	RPF2AJD	RPF2BJD
RUMC2AB2BD	RUMC3AB2BD	RUMC3GB2BD	RUMF2AB2BD	RUMF3AB2BD		RPM12BD	RPM22BD	RPM32BD	RPM42BD	RPF2ABD	RPF2BBD
RUMC2AB2ED	RUMC3AB2ED	RUMC3GB2ED	RUMF2AB2ED	RUMF3AB2ED		RPM12ED	RPM22ED	RPM32ED	RPM42ED	–	–
–	–	–	–	–		–	–	–	–	–	–
RUMC2AB2FD	RUMC3AB2FD	–	RUMF2AB2FD	RUMF3AB2FD		RPM12FD	RPM22FD	RPM32FD	RPM42FD	RPF2AFD	RPF2BFD
RUMC2AB2B7	RUMC3AB2B7	RUMC3GB2B7	RUMF2AB2B7	RUMF3AB2B7		RPM12B7	RPM22B7	RPM32B7	RPM42B7	RPF2AB7	RPF2BB7
RUMC2AB2E7	RUMC3AB2E7	RUMC3GB2E7	RUMF2AB2E7	RUMF3AB2E7		RPM12E7	RPM22E7	RPM32E7	RPM42E7	–	–
RUMC2AB2F7	RUMC3AB2F7	RUMC3GB2F7	RUMF2AB2F7	RUMF3AB2F7		RPM12F7	RPM22F7	RPM32F7	RPM42F7	RPF2AF7	RPF2BF7
–	–	–	–	–		–	–	–	–	–	–
RUMC2AB2P7	RUMC3AB2P7	RUMC3GB2P7	RUMF2AB2P7	RUMF3AB2P7		RPM12P7	RPM22P7	RPM32P7	RPM42P7	RPF2AP7	RPF2BP7
–	–	–	–	–		–	–	–	–	–	–

	For universal relays RUM					For power relays RPM				For power relays RPF	
	RUZC2M	RUZC3M	RUZC3M	–	–	RPZF1	RPZF2	RPZF3	RPZF4	–	
	–	–	–	–	–	–	–	–	–	–	
	RUZSC2M	RUZSC3M	RUZSC3M	RUZSF3M	RUZSF3M	–	–	–	–	–	
						1 and 2 poles		3 and 4 poles			
	RUW240BD					RXM040W		RUW240BD		–	
	–					RXM041BN7		–		–	
	RUW241P7					RXM041FU7		RUW241P7		–	
	–					RXM021RB		–		–	
	–					RXM021BN		–		–	
	–					RXM021FP		–		–	
	RUW242B7					RUW242B7		–		–	
	RUW242P7					–		RUW242P7		–	
	RUW101MW					–		RUW101MW		–	
	–					–				–	
	RUZC200					RPZF1 (for 1 pole relays)				–	
	RUZL420					–				–	
	RUZS2					–				–	
	–					RPZ1DA	RXZE2DA	RPZ3DA	RPZ4DA	–	
	–					RPZ1FA	RXZE2FA	RPZ3FA	RPZ4FA	–	

(4) 30A with 13 mm space between relays; 25 A when relay mounting side by side

(5) Max 10 A operating

(6) With LED

Zelio Analog

Analogue Interface
Universal Thermocouple



Type	Thermocouple				
Temperature range	0...150 °C 32...302 °F	0...300 °C 32...572 °F	0...600 °C 32...1112 °F	0...600 °C 32...1112 °F	0...1200 °C 32...2192 °F
Output range	0...10 V / 0...20 mA - 4...20 mA Switchable				
Dimensions H x W x D	80 x 22,5 x 80 mm				
Voltage	24 VDC - Non isolated				
References	RMTJ40BD	RMTJ60BD	RMTJ80BD	RMTK80BD	RMTK90BD

Universal PT 100



Type	PT 100				
Temperature range	-40...40 °C -40...104 °F	-100...100 °C -148...212 °F	0...100 °C 32...212 °F	0...250 °C 32...482 °F	0...500 °C 32...932 °F
Output range	0...10 V / 0...20 mA - 4...20 mA Switchable				
Dimensions H x W x D	80 x 22,5 x 80 mm				
Voltage	24 VDC - Non isolated				
References	RMPT10BD	RMPT20BD	RMPT30BD	RMPT50BD	RMPT70BD

Optimum PT 100



Type	PT 100				
Temperature range	-40...40 °C -40...104 °F	-100...100 °C -148...212 °F	0...100 °C 32...212 °F	0...250 °C 32...482 °F	0...500 °C 32...932 °F
Output range	0...10 V				
Dimensions H x W x D	80 x 22,5 x 80 mm				
Voltage	24 VDC - Non isolated				
References	RMPT13BD	RMPT23BD	RMPT33BD	RMPT53BD	RMPT73BD

Universal Analog Converter



Type	Analog Converter			
Input range	0...10 V or 4...20 mA	0...10 V / -10...+10 V 0...20 mA 4...20 mA	0...50 V / 0...300 V 0...500 V	0...1,5 A / 0...5 A 0...15 A
Output range	0...10 V or 4...20 mA	0...10 V / -10...+10 V 0...20 mA 4...20 mA Switchable	0...10 V 0...20 mA 4...20 mA Switchable	0...10 V or 0...20 mA ou 4...20 mA
Dimensions H x W x D	80 x 22,5 x 80 mm			80 x 45 x 80 mm
Voltage	24 VDC - Non isolated	24 VDC - Isolated	24 VDC - Isolated	24 VDC - Isolated
References	RMCA22BD	RMCA55BD	RMCA60BD	RMCA61BD

Zelio Control

Relays

3-phase monitoring relays



Function	presence of phase +phase sequence		+phase sequence, +regeneration +phase unbalance, +under/over voltage	
Monitoring voltage range	208...480 VAC	208...440 VAC	208...480 VAC	220 ... 440 VAC
Outputs	1 C/O	2 C/O	1 C/O	2 C/O
References	RM17TG00	RM17TG20	RM17TE00	RM35TF30



Function	presence of phase +under/over voltage		+presence of neutral +under/over voltage
Monitoring voltage range	208...480 VAC	220...480 VAC	120...277 VAC (phase-neutral)
Outputs	1 C/O	2 C/O	2 C/O
References	RM17UB310	RM35UB330	RM35UB3N30

Level / Speed monitoring relays



Function	Conductive liquid level monitoring	Non-conductive material level monitoring	Over/under Speed monitoring
Power supply	24...240 VAC/DC		
Monitoring range	0,25...5 K Ω 5...100 K Ω 0,05...1 M Ω	Input of sensor : Contact / PNP / NPN	Interval between pulses: 0.05...0.5 s, 0.1...1 s, 0.5...5 s 1...10 s, 0.1...1 mn, 0.5...5 mn 1...10 mn
Output	2 C/O	1 C/O	1 C/O
Reference	RM35LM33MW	RM35LV14MW	RM35S0MW

Current / Voltage /Frequency monitoring relays



Function	Voltage Monitoring Under or Over Voltage		
Power Supply	24...240 VAC/DC 50/60Hz		
Monitoring range	0.05...0.5 V	1...10 V	15...150 V
	0.3...3 V	5...50 V	30...300 V
	0.5...5 V	10...100 V	60...600 V
Outputs	2 C/O	2 C/O	2 C/O
References	RM35UA11MW	RM35UA12MW	RM35UA13MW



Function	Voltage Monitoring Under or Over Voltage			Under and Over Voltage	
Power Supply	self powered			self powered	
Monitoring range	9...15 VDC	20...80 VAC/DC	65...260 VAC/DC	20...80 VAC/DC	65...260 VAC/DC
Outputs	1 C/O	1 C/O	1 C/O	1 C/O	1 C/O
References	RM17UAS14	RM17UAS16	RM17UAS15	RM17UBE16	RM17UBE15



Function	Current Monitoring		Frequency Monitoring
	over current	over or under current	Over or under frequency
Power supply	24...240 VAC/DC	24...240 VAC/DC 50/60 Hz	120...277 VAC 50/60 Hz
Monitoring range	2...20 A	2...20 mA	0.15...1.5 A
	built-in CT	10...100 mA	0.5...5 A
		50...500 mA	1.5...15 A
Output	1 C/O	2 C/O	2 C/O
Reference	RM17JC00MW	RM35JA31MW	RM35JA32MW
			RM35HZ21FM

Zelio Control

Relays

Lift / Pump / Motor monitoring relays



Function	Lift motor room temperature monitoring		+phase presence +phase sequence
Power supply	24...240 VAC/DC 50/60Hz		
Monitoring range	input PT100 3 wires Under -1...+11 °C Over +34...+46 °C		208...480 VAC 50/60Hz input PT100 3 wires Under -1...+11 °C Over +34...+46 °C
Output	1 C/O	2 NO	2 C/O
Reference	RM35ATL0MW	RM35ATR5MW	RM35ATW5MW



Function	Pump protection Current monitor +3 phase monitor	Motor Protection Winding Temperature monitor +3 phase monitor	
Power supply	self powered (single phase :230 VAC 50/60 Hz)	24...240 VAC/DC	
Monitoring range	Current: 0.1...10 A Voltage (three phase): 208...480 VAC 50/60Hz	Winding Temperature: PTC sensor Three phase voltage: 208...480 VAC 50/60Hz	
Output	1 C/O	2 NO	2 NO
Reference	RM35BA10	RM35TM50MW	RM35TM250MW

Control relays for 3-phase supplies



Function	Rotational direction and presence of phases					
		+ Undervoltage	+ Over and undervoltage	+ Asymmetry		
Adjustable time delay	without	without	0.1...10 s	0.1...10 s	fixed, 0.5 s	0.1...10 s
Supply voltage	220...440V	380...440V	400V	380...440V	380...440V	380...440V
Output	2 C/O	2 C/O	2 C/O	2 C/O	1 C/O	2 C/O
References	RM4TG20	RM4TU02	RM4TR34 (1)	RM4TR32 (2)	RM4TA02	RM4TA32

(1) Relay with fixed voltage thresholds.

(2) Relay with adjustable voltage thresholds.

Current and voltage measurement relays

(3) Basic reference. To be completed with the letters indicating the required voltage, as shown below:

Voltage	VAC, 50/60 Hz	VDC
24...240 V	MW	MW
110...130 V	F	—
220...240 V	M	—
380...415 V	Q	—



Function	Detection of over and undercurrent					
Measuring range	3...30 mA 10...100 mA 0.1...1 A	0.3...1.5 A 1...5 A 3...15 A	0.05 ...0.5 V 0.3 ...3 V 0.5...5 V	1...10 V 5...50 V 10...100 V	30...300 V 50...500 V	180...270 V
Adjustable time delay	0.05...30 s	0.05...30 s	0.05...30 s	0.05...30 s	0.05...30 s	0.1...10 s
Output	2 C/O	2 C/O	2 C/O	2 C/O	2 C/O	2 C/O
References	RM4JA31** (3)	RM4JA32** (3)	RM4UA31** (3)	RM4UA32** (3)	RM4UA33** (3)	RM4UB35

(4) Basic reference. To be completed with the letters indicating the required voltage, as shown below:

Voltage	RM4-LG01	RM4-LA32	
	VAC, 50/60 Hz	VAC, 50/60 Hz	VDC
24 V	B	B	—
24...240 V	—	MW	MW
110...130 V	F	F	—
220...240 V	M	M	—
380...415 V	Q	Q	—



Liquid level control relays

Control relays	Empty or fill	
Sensitivity scale	5 ... 100 kΩ	0.25 ... 5 kΩ 2.5 ... 50 kΩ 25 ... 500 kΩ
Time delay	without	adjustable, 0.1 to 10 s
Output	1 C/O	2 C/O
References	RM4LG01• (4)	RM4LA32** (4)

Liquid level control probe type	Measuring electrode and reference electrode	1 simple stainless steel electrode in PVC protective casing
Mounting	suspended	suspended
Maximum operating temperature	100°C	100°C
References	LA9RM201	RM79696043

Zelio Count _____ Counters Totalisers



Display	Mechanical				LCD
Supply voltage	24 VDC				Battery
Number of digits displayed	5	6	6	8	8
Counting frequency	20 Hz	10 Hz	25 Hz	25 Hz	7.5 kHz
Type of zero reset	Manual	Without	Manual	Without	Manual (1)
Front face dimensions, W x H	41.5 x 31 mm	30 x 20 mm	60 x 50 mm	60 x 50 mm	48 x 24 mm
References	XBKT50000U10M	XBKT60000U00M	XBKT60000U10M	XBKT80000U00M	XBKT81030U33E

(1) With electrical interlocking.

Hour counters



Display	Mechanical		LCD
Supply voltage	24 VAC	230 VAC	Battery
Number of digits / display	7 (99,999.99 h)	7 (99,999.99 h)	8 (999,999.99 h)
Supply frequency	50 Hz	50 Hz	Mode: 1/100 hour
Type of zero reset	Without	Without	Manual (1)
Front face dimensions, W x H	48 x 48 mm	48 x 48 mm	48 x 24 mm
References	XBKH70000004M	XBKH70000002M	XBKH81000033E

Zelio Count

Counters

Multifunction counters



Display			LCD		LED	
Number of digits displayed			6			
Counting frequency			5 kHz			
Type of reset			Manual, electric and automation			
Front face dimensions, W x H			48 x 48 mm			
Preselection number			1	2	1	2
References	Supply voltage	24 VDC	XBKP61130G30E	XBKP61230G30E	XBKP62130G30E	XBKP62230G30E
		115 VAC	XBKP61130G31E	XBKP61230G31E	—	—
		230 VAC	XBKP61130G32E	XBKP61230G32E	XBKP62130G32E	XBKP62230G32E



Type of modular timer width 17.5 mm, relay output	On-delay	Multifunction		
External control	no	–	–	–
Supply voltage	24 VDC - 24 ...240 VAC	24 VDC - 24 ...240 VAC		12 ... 240VAC/DC
Timing range	0.1 s...100 h	0.1 s...100 h	0.1 s...10 h	0.1 s...100 h
Output	1 C/O	1 C/O	1 C/O	1 C/O
References	RE11RAMU	RE11RMMU (1)	RE11RMEMU (2)	RE11RMMW (1)

(1) Multifunction: On-delay, Off-delay, Totaliser, Symmetrical flashing, Chronometer, Pulse on energisation, Pulse output, Timing after closing/opening of control contact.

(2) Multifunction: On-delay, Off-delay, Totaliser, Symmetrical flashing, Chronometer, Pulse on energisation.



Type of modular timer width 17.5 mm, relay output	Asymmetrical flashing	Pulse on energisation	Off delay	Timing on impulse
External control	–	–	–	–
Supply voltage	24 VDC - 24...240 VAC	24 VDC - 24...240 VAC	24 VDC - 24...240 VAC	24 VDC - 24...240 VAC
Timing range	0.1 s...100 h	0.1 s...100 h	0.1 s...100 h	0.1 s...100 h
Output	1 C/O	1 C/O	1 C/O	1 C/O
References	RE11RLMU	RE11RHMU	RE11RCMU	RE11RBMU



Type of modular timer width 17.5 mm, solid-state output	On-delay	Off-delay	Multifunction (3)
Supply voltage	24...240 VAC/DC	24...240 VAC	24...240 VAC
Timing range	0.1 s...100 h	0.1 s...100 h	0.1 s...100 h
Output	solid-state	solid-state	solid-state
References	RE11LAMW	RE11LCBM	RE11LMBM

(3) Multifunction: On-delay, Off-delay, Totaliser, Symmetrical flashing, Chronometer, Pulse on energisation, Pulse output, Timing after closing/opening of control contact.



Panel-mounted relays	Timer on-delay	Asymmetrical flasher	Multifunction (4)	Multifunction (5)
Power supply	24...240 VAC/DC			
Time range	0,02 s...300 h			
Output	2 relay 5 A			
Reference	RE48ATM12MW	RE48ACV12MW	RE48AMH13MW (6)	RE48AML12MW
Back panel mounting socket	RUZC2M	RUZC3M	RUZC2M	RUZC3M
Front panel mounting socket	RE48ASOC8SOLD	RE48ASOC11SOLD	RE48ASOC8SOLD	RE48ASOC11SOLD

(4) Timer on-delay / pulse on energization

(5) Timer on-delay / calibrator / timer off-delay / symmetrical flasher

(6) 1 selectable in instantaneous

Industrial timers



Type of single function relay width 22.5 mm, relay output	On-delay		Off-delay		
External control	no	yes	no	yes	yes
Supply voltage	24 VAC/DC 110...240 VAC	24 VAC/DC 42...48 VAC/DC 110...240 VAC	24...240 VAC/DC	24 VAC/DC 42...48 VAC/DC 110...240 VAC	24 VAC/DC 42...48 VAC/DC 110...240 VAC
Timing range	0.05 s...300 h	0.05 s...300 h	0.05 s...10 mn	0.05 s...300 h	0.05 s...300 h
Output	1 C/O	2 C/O (1)	1 C/O	2 C/O (1)	1 C/O
References	RE7TL11BU	RE7TP13BU	RE7RB11MW	RE7RL13BU	RE7RM11BU

(1) 1 selectable in instantaneous mode.



Type of relay width 22.5 mm, relay output	Single function		Multifunction	
	Asymmetrical flashing	Pulse on energisation	6 functions (2)	8 functions (3)
External control	yes	no	—	—
Supply voltage	24 VAC/DC 42...48 VAC/DC 110...240 VAC	24 VAC/DC 110...240 VAC	24 VAC/DC 42...48 VAC/DC 110...240 VAC	24 VAC/DC 110...240 VAC
Timing range	0.05 s...300 h	0.05 s...300 h	0.05 s...300 h	0.05 s...300 h
Output	1 C/O	1 C/O	1 C/O	2 C/O (4)
References	RE7CV11BU	RE7PE11BU	RE7ML11BU	RE7MY13BU

(2) RE7ML11BU functions: On-delay, Off-delay, Pulse on energisation with start on energisation, Pulse on energisation with start on opening of remote control contact, Flashing with start during the OFF period, Flashing with start during the ON period.

(3) REMY13BU functions: On-delay, Off-delay, Pulse on energisation with start on energisation, Pulse on energisation with start on opening of remote control contact, Flashing with start during the OFF period, Flashing with start during the ON period, Star-delta starting with double On-delay timing, Star-delta starting with contact for switching to star connection.

(4) 1 selectable in instantaneous mode

Miniature plug-in relays, relay output



Functions				
Timing ranges	7 switchable ranges	0.1 s...1 s - 1 s...10 s - 0.1 min...1 min - 1 min...10 min - 0.1 h...1 h - 1 h...10 h - 10 h...100 h		
Relay output		4 timed C/O contacts		2 timed C/O contacts
Rated current		3 AC 5 A		AC 5 A
Voltages	24 VDC	RE XL4TMBD		RE XL2TMBD
	24 VAC 50/60 Hz	RE XL4TMB7		RE XL2TMB7
	120 VAC 50/60 Hz	RE XL4TMF7		RE XL2TMF7
	230 VAC 50/60 Hz	RE XL4TMP7		RE XL2TMP7
Socket with mixed contact terminals	With screw clamp	RXZE2M114		RXZE2M114
	With connector	RXZE2M114M		RXZE2M114M



Compact smart relays	With display, a.c. power supply					
Supply voltage	24 VAC		100...240 VAC			
Number of inputs/outputs	12	20	10	12	20	20
Number of inputs	8	12	6	8	12	12
Discrete inputs						
Number of outputs	4 relay	8 relay	4 relay	4 relay	8 relay	8 relay
Dimensions, W x D x H (mm)	71.2x59.5x107.6	124.6x59.5x107.6	71.2x59.5x107.6		124.6x59.5x107.6	
Clock	yes	yes	no	yes	no	yes
References	SR2B121B	SR2B201B	SR2A101FU (1)	SR2B121FU	SR2A201FU (1)	SR2B201FU

(1) Programming on smart relay in LADDER language only



Compact smart relays	With display, d.c. power supply					
Supply voltage	12 VDC		24 VDC			
Number of inputs/outputs	12	20	10	12	20	20
Number of inputs	8	12	6	8	12	12
Discrete inputs						
including 0-10 V analogue inputs	4	6	-	4	2	6
Number of outputs	4 relay	8 relay	4 relay	4	8 relay	8
Dimensions, W x D x H (mm)	71.2x59.5x107.6	124.6x59.5x107.6	71.2x59.5x107.6		124.6x59.5x107.6	
Clock	yes	yes	no	yes	no	yes
References	SR2B121JD	SR2B201JD	SR2A101BD (1)	SR2B121BD (2)	SR2A201BD (1)	SR2B201BD (2)

(1) Programming on smart relay in LADDER language only

(2) Replace the ● by number 1 to order a smart relay with **relay output** or by 2 for a smart relay with **transistor output** (Example: SR2B121BD)



Compact smart relays	Without display and without buttons					
Supply voltage	100...240 VAC			24 VDC		
Number of discrete inputs/outputs	10	12	20	10	12	20
Number of inputs	6	8	12	6	8	12
Discrete inputs						
including 0-10 V analogue inputs	-	-	-	-	4	6
Number of outputs	4 relay	4 relay	8 relay	4 relay	4 relay	8 relay
Dimensions, W x D x H (mm)	71.2x59.5x107.6		124.6x59.5x107.6	71.2x59.5x107.6		124.6x59.5x107.6
Clock	no	yes	yes	no	yes	yes
References	SR2D101FU (1)	SR2E121FU	SR2E201FU	SR2D101BD (1)	SR2E121BD (3)	SR2E201BD (3)

(1) Programming on smart relay in LADDER language only

(3) To order a smart relay for a **24 VAC supply** (no analogue inputs), delete the letter **D** from the end of the reference (**SR2E121B** and **SR2E201B**)

Modular, SR3



Modular smart relays*		With display						
Supply voltage		24 VAC		100...240 VAC		12 VDC	24 VDC	
Number of inputs/outputs		10	26	10	26	26	10	26
Number of inputs	Discrete inputs	6	16	6	16	16	6	16
	including 0-10 V analogue inputs	—	—	—	—	6	4	6
Number of outputs		4 relay	10 relay	4 relay	10 relay	10 relay	4	10
Dimensions, W x D x H (mm)		71.2x59.5x107.6	124.6x59.5x107.6	71.2x59.5x107.6	124.6x59.5x107.6	124.6x59.5x107.6	71.2x59.5x107.6	124.6x59.5x107.6
Clock		yes	yes	yes	yes	yes	yes	yes
References		SR3B101B	SR3B261B	SR3B101FU	SR3B261FU	SR3B261JD	SR3B10BD (1)	SR3B26BD (1)

*The modular base can be fitted with one I/O extension module. The 24 VDC modular base can be fitted with one communication module and/or one I/O extension module

(1) Replace the ● by number 1 to order a smart relay with **relay output** or by 2 for a smart relay with **transistor output** (Example: SR3B101BD)



Extension modules for Zelio Logic SR3B●●●●● (2)		Communication		Discrete Inputs/Outputs			Analogue Inputs/Outputs
Network		Modbus	Ethernet	—			—
Number of inputs/outputs		—	—	6	10	14	4
Number of inputs	Discrete	—	—	4	6	8	—
	Analogue (0...10 V, 0...20 mA, PT100)	—	—	—	—	—	2 (1 PT100 max.)
Number of outputs	Relay	—	—	2 relay	4 relay	6 relay	—
	Analogue (0...10 V)	—	—	—	—	—	2
Dimensions, W x D x H (mm)		35.5x59.5x107.6		35.5x59.5x107.6	72x59.5x107.6		35.5x59.5x107.6
References	24 VAC	—	—	SR3XT61B	SR3XT101B	SR3XT141B	—
	100...240 VAC	—	—	SR3XT61FU	SR3XT101FU	SR3XT141FU	—
	12 VDC	—	—	SR3XT61JD	SR3XT101JD	SR3XT141JD	—
	24 VDC	SR3MBU01BD	SR3NET01BD	SR3XT61BD	SR3XT101BD	SR3XT141BD	SR3XT43BD

(2) The power supply of the extension modules is provided via the Zelio Logic modular relays

Zelio Soft 2 software and programming tools



Zelio Soft 2 software, connecting cables, wireless connecting, memory	Multilingual programming software	Connecting cables		Wireless connection	Back-up memory
Description	PC CD-ROM (Windows 98, NT, 2000, XP) (3)	Serial PC/Smart relay	USB PC/Smart relay	Bluetooth interface	EEPROM
References	SR2SFT01	SR2CBL01	SR2USB01	SR2BTC01	SR2MEM02

(3) CD-ROM including Zelio Soft 2 programming software, an application library, a self-training manual, installation instructions and a user's manual

Communication interface for SR2/SR3

Interface, modems, Zelio Logic Alarm software	Communication interface	Modems (4)		Alarm management software
Supply voltage	12...24 VDC	12...24 VDC	12...24 VDC	—
Description	—	Analogue modem	GSM modem	PC CD-ROM (Windows 98, NT, 2000, XP)
Dimensions, W x D x H (mm)	72x59.5x107.6	120.7x35x80.5	111x 25.5x54.5	—
References	SR2COM01	SR2MOD01	SR2MOD02	SR2SFT02

(4) Must be used in conjunction with communication interface SR2COM01



Simplicity, ease of use



Type of base		Compact			
Number of digital I/O		10	16	24	40
Number of digital inputs (24 VDC)		6 sink/source	9 sink/source	14 sink/source	24 sink/source
Number of digital outputs		4 relay (2 A)	7 relay (2 A)	10 relay (2 A)	14 relay (2 A), 2 solid-state (1 A)
Type of connection		Screw terminals (non removable)			
Possible I/O expansion modules		–	–	4	7
Counting		3 x 5 kHz, 1 x 20 kHz			
PWM positioning		–			
Serial ports		1 x RS 485	1 x RS 485; option: 1 x RS 232C or RS 485		
Protocol		Modbus master/slave, ASCII, I/O relocation			
Ethernet port		–	–	–	RJ45 Ethernet
Dimensions, W x D x H		80 x 70 x 90 mm	80 x 70 x 90 mm	95 x 70 x 90 mm	157 x 70 x 90 mm
References	Supply voltage 100...240 VAC	TWDLCAA10DRF	TWDLCAA16DRF	TWDLCAA24DRF	TWDLCAE40DRF (1)
	Supply voltage 19.2...30 VDC	TWDLCA10DRF	TWDLCA16DRF	TWDLCA24DRF	TWDLCE40DRF (1)
	Real-time clock (option)	TWDXCPRTC			
	Display unit (option)	TWDXCPODC			
	Memory cartridge (option)	TWDXCPMF32 (3)			TWDXCPMF64 (4)

(1) 40 I/O version without Ethernet also available: TWDLCAA40DRF and TWDLCA40DRF



Compactness, flexibility



Type of base		Modular		
Number of digital i/O		20		40
Number of digital inputs (24 VDC)		12 sink/source	12 sink/source	24 sink/source
Number of digital outputs		8 transistor, source (0.3 A)	6 relay (2 A) & 2 trans., source (0.3 A)	16 transistor, source (0.3 A)
Type of connection		HE10 connector	Removable screw terminals	HE10 connector
Possible I/O expansion modules		4	7	7
Supply voltage		24 VDC		
Counting		2 x 5 kHz, 2 x 20 kHz		
PLS/PWM positioning		2 x 7 kHz		
Serial ports		1 x RS 485; option: 1 x RS 232C or RS 485		
Protocol		Modbus master/slave, ASCII, I/O relocation		
Dimensions, W x D x H		35.4 x 70 x 90 mm	47.5 x 70 x 90 mm	47.5 x 70 x 90 mm
References		TWDLMDA20DTK (2)	TWDLMDA20DRT	TWDLMDA40DTK (2)
	Real-time clock (option)	TWDXCPRTC		
	Display unit (option)	TWDXCPODM		
	Memory cartridge (option)	TWDXCPMF32 (3)	TWDXCPMF64 (4)	

(2) Sink version transistor outputs also available: TWDLMDA20DUK and TWDLMDA40DUK

(3) Application backup, program transfer

(4) Memory expansion, application backup, program transfer

Programmable controllers

I/O modules

New



Type of module		Analogue inputs				
Number of inputs		2 I	2 I	4 I	8 I	8 I
Connection		Removable screw terminals				
Inputs	Range	Thermocouples type K, J, T	0...10 V (1) 4...20 mA (2)	0...10 V (1) 4...20 mA (2) θ °C	0...10 V (1) 4...20 mA (2)	PTC/NTC
	Resolution	12 bits (4096 points)			10 bits (1024 points)	
Measuring accuracy		0.2% of the full scale value				
Supply voltage		24 VDC				
Dimensions, W x D x H		23.5 x 70 x 90 mm				
References		TWDAMI2LT	TWDAMI2HT	TWDAMI4LT	TWDAMI8HT	TWDARI8HT

(1) Non differential

(2) Differential



New



Type of module		Analogue Outputs, Inputs/Outputs (mixed)				
Number of inputs and/or outputs		1 O	2 O	2 I / 1 O	2 I / 1 O	4 I / 2 O
Connection		Removable screw terminals				
Inputs	Range	—	—	0...10 V (1) 4...20 mA (2)	Thermocouple type K, J & T 3-wire Pt 100 thermal probe	0...10 V (1) 4...20 mA (2)
	Resolution	—	—	12 bits (4096 points)	12 bits (4096 points)	12 bits (4096 points)
Outputs	Range	0...10 V (1) 4...20 mA (2)	± 10 V	0...10 V (1) 4...20 mA (2)	0...10 V (1) 4...20 mA (2)	0...10 V (1) 4...20 mA (2)
	Resolution	12 bits	11 bits + sign	12 bits	12 bits	12 bits
Measuring accuracy		0.2% of the full scale value				
Supply voltage		24 VDC				
Dimensions, W X D x H		23.5 x 70 x 90 mm				
References		TWDAMO1HT	TWDAVO2HT	TWDAMM3HT	TWDALM3LT	TWDAMM6HT

(1) Non differential

(2) Differential



Type of module		Digital Inputs/Outputs					
Number of inputs and/or outputs		8	16	16	32	4 I / 4 O	16 I / 8 O
Connection		Removable screw terminals		HE10 connectors		Removable screw terminals	Spring terminals (non removable)
References	Inputs	24 VDC sink	TWDDI18DT	—	—	—	—
		24 VDC sink/source	—	TWDDI16DT	TWDDI16DK	TWDDI32DK	—
		120 V sink	TWDDAI8DT	—	—	—	—
	Outputs	Relay (2 A)	TWDDRA8RT	TWDDRA16RT	—	—	—
		Transistor, source (0.1 A)	TWDDO8TT (3)	—	TWDDO16TK (3)	TWDDO32TK (3)	—
	Inputs, 24 VDC sink/source + Outputs, relay (2 A)		—	—	—	—	TWDDMM8DRT TWDDMM24DRF

(3) Sink version transistor outputs also available: TWDDO8UT, TWDDO16UK and TWDDO32UK



Type of module	Serial interface			Serial interface adaptor		
Physical layer (non isolated)	RS 232C	RS 485		RS 232C	RS 485	
Connection	Mini-DIN connector		Screw terminals	Mini-DIN connector		Screw terminals
Protocol	Modbus master/slave, ASCII, I/O relocation					
Twido base compatibility	Modular base TWDLMDA			Compact base TWDLCAA16/24DRF Modular base via integrated display module TWDXCPDM		
References	TWDNOZ232D	TWDNOZ485D	TWDNOZ485T	TWDNAC232D	TWDNAC485D	TWDNAC485T



Type of module	CANopen expansion	Ethernet interface	Modbus isolation module	Modbus junction module	AS-Interface master
Number of modules	1	1	–	–	2 (1)
Connection	SUB-D9	RJ45	RJ45	RJ45	Removable screw terminals
Twido base compatibility	20, 24 or 40 I/O base	All models	All models	All models	20, 24 or 40 I/O base
References	TWDNCO1M	499TWD01100	TWDXCAISO	TWDXCAT3RJ	TWDNOI10M3

(1) 2 modules max., 62 digital slaves max., 7 analogue slaves max., AS-Interface/M3, V 2.11 (profile S.7.4 not supported)

Programming software



Software, connecting cables, interfaces	TwidoSuite software V1.0 EN/FR	TwidoAdjust software	Connecting cables		Bluetooth® USB adaptor	Bluetooth® gateway
Application	PC with Windows 2000® or XP	Pocket PC 2003 or 2005	Twido/PC USB port	Twido/PC serial port	For PC not fitted with Bluetooth®	For Twido controller
References	TWDBTFU10EF(2)	TWDSMD1002V30M	TSXCUSB485	TSXPCX1031 (3)	VW3A8115	VW3A8114

(2) For other languages, replace the last 2 letters of the reference (EF) by the following letters: ES for English-Spanish, ET for English-Italian, ED for English-German or EC for English-Chinese (simplified).

(3) For Twido Extreme: order the reference VW3A8106

Programmable controllers

Bases

New



Robustness



Type of base		Twido Extreme
Number of I/O		41
Degree of protection		IP67
Temperature		-40...+110°C, storage -55...+155°C
Relative humidity		90% without condensation
Number of inputs	Digital	13 (short-circuit protected)
	Analogue	8 (including 1 input configurable to PWM)
	PWM	1
Number of outputs	Digital	16* (short-circuit protected)
	PWM or PLS	3
Supply voltage		12 or 24 VDC
Counting		1 x 10 kHz
Communication ports		RS 485, CAN J1939, CANopen master
Serial link protocols		Modbus RTU master/slave, ASCII
Dimensions, W x D x H		165.51 x 45.70 x 225 mm
References		TWDLCDCK1

* 16 outputs in 12 VDC. Limited to 8 outputs in 24 VDC.



Fixing and connection	Fixing kit	70-pin connector	Pre-wired 70-pin connector
Details	4 spacers, 8 washers, 8 shock mounts	80 pins, 80 blanking plugs, 1 cover	Pre-wired with 1.5 m long cable, free wires other end
Degree of protection	–	IP67	IP67
References	TWDXMTK4	TWDFCNK70	TWDFCWK70L015

Separate components	Crimping tool	RJ45 programming connector
Application	Crimping wires onto pins of 70-pin connector	Connecting Twido Extreme to a programming PC
References	TWDXMTCT	TWDNAK70P

Modicon TSX Micro

Automation platform

Basic configurations



Type of processor		TSX 3705	TSX 3708	TSX 3710	
Power supply		110...240 VAC		24 VDC	
Number of slots	Standard	2 (1 available)	3 (1 available)	2 (1 available)	
	On extension	–	–	2	
Number of integrated discrete I/O modules		1 (16 I, 12 Q)	2 (32 I, 24 Q)	1 (16 I, 12 Q)	1 (16 I, 12 Q)
Number of integrated analog I/O channels		–	–	–	–
Type of integrated I/O		I: 24 VDC, Q: relay	I: 24 VDC, Q: relay	I: 24 VDC, Q: sol.st. 0.5 A	I: 24 VDC, Q: relay
Application-specific modules (counter, position control)		2 half-size		2 half-size	
Bus	AS-Interface cabling system	–		1 half-size	
	CANopen machine bus	–		–	
	Fipio fieldbus	–		–	
Networks	Modbus Plus, Fipway	–		–	
	Ethernet TCP/IP	–		1 external module	
Memory capacity	Integrated	11 K words		14 K words	
	With PCMCIA extension	–		–	
Execution time for one instruction	Boolean	0.25 µs		0.25 µs	
	Numerical	4.81 µs		4.81 µs	
Rack dimensions (WxDxH)		170,3 x 132,5 x 151 mm	230 x 132,5 x 151 mm	170,3 x 132,5 x 151 mm	
Reference	With screw terminals	TSX3705028DR1	TSX3708056DR1	TSX3710128DT1	TSX3710128DR1
	With HE 10 connector (1)	–	–	TSX3710128DTK1	–

(1) For use with Advantys Telefast ABE7 wiring system

(2) Basic configuration provided without I/O modules

Memory extension



Type of PCMCIA card for TSX 3721/22		Application		
Technology		SRAM	Flash EPROM	Backup
Memory size (3)	32 K words	TSXMRPP128K	TSXMFPP128K	TSXMFPP096K
	32 K words/128 K words	TSXMRPP348K	TSXMCPC224K	–
	64 K words	TSXMRPP224K	TSXMFPP224K	–
	64 K words/128 K words	TSXMRPP384K	TSXMCPC224K	–
	128 K words	TSXMRPC448K	TSXMFPP384K	–
	128 K words/128 K words	TSXMRPC768K	–	–

(3) The 1st value corresponds to the size of the application area, the second to the size of the area for data storage (recipes, production data, etc).



TSX 3710			TSX 3721		TSX 3722	
24 VDC	110...240 VAC		24 VDC	110...240 VAC	24 VDC	110...240 VAC
2 (1 available)			3 (3 available)		3 (3 available)	
2			2		2	
2 (32 I, 32 Q)	1 (16 I, 12 Q)	1 (16 I, 12 Q)	–		–	
–	–	–	–		1 (8 I, 1 Q)	
I: 24 VDC, Q: sol. st. 0.1 A	I: 115 VAC, Q: relay	I: 24 VDC, Q: relay	–		I: 0...10 V or 0/4...20 mA, Q: 0...10 V	
2 half-size			4 half-size		4 half-size (2 integrated channels)	
1 half-size			1 half-size		1 half-size	
–			1 PCMCIA card		1 PCMCIA card	
–			1 PCMCIA card		1 PCMCIA card	
–			1 PCMCIA card		1 PCMCIA card	
1 external module			1 external module		1 external module	
14 K words			20 K words		20 K words	
–			128 K words + 128 K words for file storage		128 K words + 128 K words for file storage	
0.25 µs			0.13 µs (0.19 µs with PCMCIA)		0.13 µs (0.19 µs with PCMCIA)	
4.81 µs			4.50 µs		4.50 µs	
170,3 x 132,5 x 151 mm			230 x 132,5 x 151 mm			
–	TSX3710028AR1	TSX3710028DR1	TSX3721101 (2)	TSX3721001 (2)	TSX3722101 (2)	TSX3722001 (2)
TSX3710164DTK1	–	–				

Mini extension rack




Type of rack	2 slots (4 positions)
For use with	TSX3710/21/22
Rack dimensions (WxDxH)	112,5 x 132,5 x 151 mm
Reference	TSXRKZ2

Process power supplies see chapter 6 "Power supply"

Modicon TSX Micro Automation platform

Discrete I/O modules



Type of module		Discrete inputs			
Connection		By HE 10 connector (1)		By screw terminals supplied	
Module format		Half		Standard	Half
Number of channels		12		32	8
Input voltage	24 VDC positive logic	TSXDEZ12D2K	–	TSXDEZ32D2	–
	24 VDC positive/negative logic	–	TSXDEZ12D2	–	–
	100...120 VAC	–	–	–	TSXDEZ08A4
	200...240 VAC	–	–	–	TSXDEZ08A5

(1) For use with Advantys Telefast ABE7 wiring system



Type of module		Discrete outputs					
		Solid state			Relay		
Connection		By HE 10 conn. (1)		By screw terms. supplied			
Module format		Half		Standard	Half		
Number of protected channels		8		32	4	8	32
Protection of outputs		Yes		Yes	Yes	No	No
Output voltage/current	24 VDC/0.5 A	TSXDSZ08T2K	TSXDSZ08T2	TSXDSZ32T2	–	–	–
	24 VDC/2 A	–	–	–	TSXDSZ04T22	–	–
	24 VDC/1 A per channel	–	–	–	–	TSXDSZ08R5	–
	24...240 VAC/1 A per channel	–	–	–	–	–	TSXDSZ32R5

(1) For use with Advantys Telefast ABE7 wiring system



Type of module		Discrete I/O					
Connection		By HE 10 connector (1)			By screw terminals supplied		
Module format		Half	Standard				
Number of inputs		8	16	32	16	16	16
Number of outputs		8 solid state	12 solid state	32 solid state	12 solid state	12 solid state	12 solid state
Protection of outputs		Yes				No	
Voltage/current output	24 VDC/0.5 A	TSXDMZ16DTK	TSXDMZ28DTK	–	TSXDMZ28DT	–	–
	24 VDC/0.1 A	–	–	TSXDMZ64DTK	–	–	–
	100...120 VAC/50 VA	–	–	–	–	TSXDMZ28DR	TSXDMZ28AR

(1) For use with Advantys Telefast ABE7 wiring system

Analog I/O modules




Type of module	Analog inputs	
	High level with common point	High level isolated
Connection	By screw terminals supplied	
Number of channels	8	4
Resolution	11 bits + sign	12 bits
Input signal	$\pm 10\text{ V}$, $0\ldots 10\text{ V}$	$0\ldots 20\text{ mA}$, $4\ldots 20\text{ mA}$
Reference	TSXAEZ801	TSXAEZ802
		TSXAEZ414

(1) $\pm 10\text{ V}$, $0\ldots 10\text{ V}$, $0\ldots 5\text{ V}$, $1\ldots 5\text{ V}$, $0\ldots 20\text{ mA}$, $4\ldots 20\text{ mA}$, B, E, J, K, L, N, R, S, T, U, Pt 100, Ni 1000 (2 or 4-wire), thermal probe, thermocouple



Type de module	Analog outputs	
	With common point	
Connection	By screw terminals supplied	By screw terminals supplied
Number of channels	4	2
Resolution	11 bits + sign	11 bits + sign or 12 bits
Input signal	$\pm 10\text{ V}$, $0\ldots 10\text{ V}$	$\pm 10\text{ V}$, $0\ldots 20\text{ mA}$, $4\ldots 20\text{ mA}$
Reference	TSXASZ401	TSXASZ200



Type of module	Analog I/O	Analog I/O
	Integrated	High level with common point
Connection	By 15-way SUB-D connector not supplied	By screw terminals supplied
Number of inputs	8	4
Number of outputs	1	2
Resolution	8 bits	11 bits + sign or 12 bits
I/O signal	$0\ldots 10\text{ V}$, $0\ldots 20\text{ mA}$, $4\ldots 20\text{ mA}$	$\pm 10\text{ V}$, $0\ldots 10\text{ V}$, $0\ldots 20\text{ mA}$, $4\ldots 20\text{ mA}$
Reference	TSX3722 (2)	TSXAMZ600

(2) References: see pages 3/16 and 3/17, TSX3722 basic configuration

Modicon TSX Micro

Automation platform

Integrated counter modules



Type of module	Counting on discrete I/O module	Integrated counting on TSX 3722
Type of inputs for	Sensors, limit switches Totem Pole incremental encoders	Sensors, limit switches Totem Pole incremental encoders
Frequency	500 Hz	10 kHz
Response time	8 ms	8 ms
Number of channels	2 (1)	2 (2)
Reference	TSX37 (3)	TSX3722 (3)

(1) On the first 4 inputs of the 28, 32 or 64 discrete I/O modules
(2) Plus 2 channels on the discrete I/O
(3) References: see pages 3/12 and 3/13, TSX37 basic configuration

Counter/position control modules



Type of module	Counter			Positioning
Type of inputs for	2-wire PNP sensors 24 VDC Totem Pole incremental encoders 5 VDC RS 422, 10...30 VDC			SSI or parallel absolute encoder 5 VDC, 10...30 VDC
Frequency	40 kHz	40 kHz	500 kHz	200 or 1000 kHz
Response time	5 ms	5 ms		5 ms
Number of channels	1	2		1
Reference	TSXCTZ1A	TSXCTZ2A	TSXCTZ2AA	TSXCTZ1B

Communication modules



Type of module		Ethernet TCP/IP network For TSX 3710/21/22 PLCs	
Speed		10/100 MBps	10/100 MBps
Standard services		TCP/IP(Uni-TE, Modbus)	TCP/IP(Uni-TE, Modbus)
Transparent Ready	Class	B20	C20
	I/O Scanning	Yes	Yes
Web server	Standard services	Yes	Yes
	FactoryCast services	–	Yes with 8 MB of user Web pages and graphics editor
Reference		TSXETZ410	TSXETZ510



Type of module		AS-Interface cabling system	CANopen machine bus	Fipio fieldbus
Name and description		Half size in-rack	PCMCIA card	PCMCIA card
Speed		167 kBps	20 kBps...1 MBps dep. on distance	1 MBps
Reference		TSXSAZ10	TSXCPP110	TSXFPP10



Type of module		Serial links Uni-Telway, Modbus	
Name and description		Integrated port	Multiprotocol PCMCIA card
Speed		19.2 kBps	1.2...19.2 kBps
Reference	With interface RS 485	TSX37 (1)	TSXSACP114
	RS 232D	–	TSXSACP111
	20 mA CL	–	TSXSACP112

(1) References: see pages 3/12 and 3/13, TSX3705/08/10 PLCs with link integrated on TER terminal port, or TSX3721/22 PLCs with link integrated on AUX terminal port.



Type of module		Networks Modbus Plus	Fipway
Name and description		PCMCIA card	PCMCIA card
Speed		1 MBps	1 MBps
Reference		TSXMBP100	TSXFPP20

Modicon M340 Automation platform

Processors modules

New



Type of processor			Standard BMX P34 1000	High-performance BMX P34 2010	BMX P34 2020	BMX P34 2030
Number of racks			1 (4, 6, 8 or 12 slots)			
Maximum configuration			Maximum 12 slots for processor and modules (excluding power supply module)			
Functions	Max. no. (1)	Discrete I/O	512	704		
		Analog I/O	66			
		Control channels	Programmable loops (via CONT-CTL process control EFB library)			
		Counter channels	20	36		
		Motion control	–	Independent axes on CANopen bus (via MFB library)	–	Independent axes on CANopen bus (via MFB library)
		Integrated connections	Ethernet TCP/IP	–		1 RJ45 port, 10/100 MBps, with Transparent Ready class B10 standard web server
		CANopen master bus	–	1 (9-way SUB-D)	–	1 (9-way SUB-D)
		Serial link	1 RJ45 port, Modbus master/slave RTU/ASCII or character mode (non isolated RS 232C/RS 485), 0.3...19.2 kBps			–
		USB port	1 port, 12 MBps			
		Communication module	Ethernet TCP/IP	1 RJ45 port, 10/100 MBps with: - Transparent Ready class B30 standard web server with BMX NOE 0100 module - Transparent Ready class C30 configuration web server with BMX NOE 0110 module		
Internal user	Total capacity		2048 Kb	4096 Kb		
RAM	Program, constants and symbols		1792 Kb	3584 Kb		
	Data		128 Kb	256 Kb		
Execution time for one instruction	Boolean		0.18 µs	0.12 µs		
	On words or fixed point arithmetic	Single-length words	0.38 µs	0.25 µs		
		Double-length words	0.26 µs	0.17 µs		
		On floating points		1.74 µs	1.16 µs	
No. of K instructions executed per ms	100% Boolean		5.4 Kinst/ms	8.1 Kinst/ms		
	65% Boolean and 35% fixed arithmetic		4.2 Kinst/ms	6.4 Kinst/ms		
System overhead	Master task		1.05 ms	0.70 ms		
	Fast task		0.20 ms	0.13 ms		
References			BMX P34 1000	BMX P34 2010	BMX P34 2020	BMX P34 2030

(1) Only affects in-rack modules. The remote I/O on the CANopen bus are not included in these maximum numbers.

Modicon M340 Automation platform

Memory cards



Type of card	8 MB memory card	8 MB memory card + files
Use	Supplied as standard with each processor. Used for: <ul style="list-style-type: none"> – Backup of program, constants, symbols and data – Activation of class B10 web server 	As replacement for the memory card supplied as standard with each processor, used for: <ul style="list-style-type: none"> – Backup of program, constants, symbols and data – File storage, 16 MB – Activation of class B10 web server
Compatibility	BMX P34 1000/20.0	BMX P34 20.0
References	BMX RMS 008MP	BMX RMS 008MPF

Communication modules



Type of module	Ethernet TCP/IP network	
Speed	10/100 MBps	
Standard services	Modbus TCP/IP messaging	TCP/IP (Uni-TE, Modbus)
Conformity class	Transparent Ready class B30	Transparent Ready class C30
Communication service	I/O Scanning service	Yes
Transparent Ready	FDR service	Yes (client/server)
	SNMP network management service	Yes
	Global Data service	Yes
	SOAP/XML Web service	No
	Passband management	Yes
References	BMX NOE 0100	BMX NOE 0110
Memory card	Compatibility	Ethernet module BMXNOE0100
	Use	Provides services conforming to Transparent Ready: <div> <div>Class B</div> <div>Class C 16 MB available for user web pages</div> </div>
References	BMX RWS B000M	BMX RWS C016M

USB connexion cordsets

Designation	Terminal port/USB cordsets	
Use	From	Mini B USB port on the Modicon M340 processor
	To	PC terminal type A USB port
Length	1.8 m	4.5 m
References	BMX XCA USB H018	BMX XCA USB H045

Modicon M340 Automation platform

Power supply modules



Type of module		Power supply modules			
Voltage		24 VDC isolated	24...48 VDC isolated	100...240 VAC	
Nominal input current		1...24 VDC	1.65...24 VDC, 0.83...48 VAC/DC	0.61...115 VAC	
Micro-break duration		≤ 1			
Integrated protection		Via internal fuse (not accessible)			
Max. useful power		17W	32 W	20 W	36 W
Max. dissipated power		8.5 W			
Removable connectors (set of 2)	supplied as standard	BMX XTS CPS10 (cage clamp)			
	to be ordered separately	BMX XTS CPS20 (spring-type)			
References		BMX CPS 2010	BMX CPS 3020	BMX CPS 2000	BMX CPS 3500

Racks



Designation	Racks			
Type of modules to be installed	BMX CPS power supply, BMX P34 processor, I/O modules and application-specific modules (counter, communication)			
No. of slots	4	6	8	12
References	BMX XBP 0400	BMX XBP 0600	BMX XBP 0800	BMX XBP 1200

Optional connection accessories

Shielding connection kit	For BMX EHC 0200/0800 modules			
	Consisting of a metal bar, 2 sub-bases for mounting on rack and a set of spring clamping rings			
Rack	BMX XBP 0400	BMX XBP 0600	BMX XBP 0800	BMX XBP 1200
References	BMX XSP 0400	BMX XSP 0600	BMX XSP 0800	BMX XSP 1200

Spring clamping rings (pack of 10)	Cables with cross-section	1.5...6 mm ²	5...11 mm ²
References		STB XSP 3010	STB XSP 3020

Protective covers (pack of 5)	
	For unoccupied slots on BMX XBP●●00 rack
References	BMX XEM 010



Type of module			DC input modules				
Number of inputs			16	16	32	64	16
Connection			Screw or spring-type 20-way removable terminal block		1 connector 40-way	2 connectors 40-way	Screw or spring-type 20-way removable terminal block
Nominal input values	Voltage		24 V	48 V	24 V		
	Current		3.5 mA	2.5 mA	1 mA	3 mA	
	Logic		Positive (<i>sink</i>)				
Input limit values	At state 1	Voltage	≥11 V	≥34 V	≥11 V	≥15 V	≥14 V
		Current	> 2 mA (for U ≥11 V)	> 2 mA (for U ≥34 V)	> 2 mA (for U ≥11 V)	> 1 mA (for U ≥5 V)	> 2 mA (for U ≥15 V)
	At state 0	Voltage	< 5 V	< 10 V	< 5 V		
		Current	≥1.5 mA	≥0.5 mA	≥1.5 mA	≥0.5 mA	
References			BMX DDI 1602	BMX DDI 1603	BMX DDI 3202K	BMX DDI 6402K	BMX DAI 1602



Type of module			AC input modules		
Number of inputs			16		
Connection			Screw or spring-type 20-way removable terminal block		
Nominal input values	Voltage		24 VAC	48 AC	100...120 VAC
	Current		3 mA		
	Frequency		50/60 Hz		
Input limit values	At state 1	Voltage	≥15 V	≥34 V	≥74 V
		Current	≥2 mA		≥2.5 mA
	At state 0	Voltage	≤5 V	≤10 V	≤20 V
		Current	≤1 mA		
References			BMX DAI 1602	BMX DAI 1603	BMX DAI 1604



Type of module		DC solid state output modules			
Number of inputs		16	16	32	64
Connection		Screw or spring-type 20-way removable terminal block		One 40-way connector	Two 40-way connectors
Nominal output values	Voltage	24 VDC			
	Current	0.5 V		0.1 V	
	Logic	Positive (<i>source</i>)	Negative (<i>sink</i>)	Positive (<i>source</i>)	
Output limit values	Voltage (ripple included)	19...30 (possible up to 34 V, limited to 1 hour in every 24 hours)			
	Current per channel	0.625 A			0.125 A
	Current per module				
Maximum dissipated power		4	2.26	3.6	6.85
References		BMX DDO 1602	BMX DDO 1612	BMX DDO 3202K	BMX DDO 6402K

Modicon M340

Automation platform

Discrete I/O modules



Type of module		Triac output modules
Number of inputs		16
Connection		Screw or spring-type 20-way removable terminal block
Operating voltage	Nominal	100...240 VAC
	Limit	85...288 VAC
Currents	Maximum	0.6 per channel, 2.4 per common, 4.8 for all 4 commons.
	Minimum	25 mA at 100 V a, 25 mA at 240 V a.
Maximum inrush current		≤ 20/cycle
Reference		BMX DAO1605



Type of module		Relay output modules	
Number of inputs		8	16
Connection		Screw or spring-type 20-way removable terminal block	
Max. operating voltage	DC	10...34 VDC	24...125 VDC (resistive load)
	AC	10...264 VAC	200...264 VAC (Cosφ = 1)
Response time	Activation	< 10 ms	
	Deactivation	< 8 ms	< 12 ms
Dissipated power		2.7 W max	3 W
References		BMX DRA 0805	BMX DRA 1605



Type of module			24 VDC mixed I/O modules				
			Inputs		Solid state outputs	Inputs	Solid state outputs
Number of I/O			8		8	16	16
Connection			Screw or spring-type 20-way removable terminal block				One 40-way connector
Input limit values		At state 1	Voltage	≥11V		≥11V	
			Current	≥3 mA (for U ≥11)		≥2 mA (for U ≥11)	
		At state 0	Voltage	5 V		5 V	
			Current	≤1.5 mA		≤1.5 mA	
Sensor power supply (ripple included)			19...30 V (possible up to 30 V, limited to 1 hour in every 24 hours)				
Output limit values		Voltage (ripple included)		19...30 (possible up to 30 V, limited to 1 hour in every 24 hours)			
		Current	per channel	0.625 A		0.125 A	
			per module	5 A		3.2 A	
Maximum dissipated power			3.7 W		4 W		
References			BMX DDM 16022			BMX DDM 3202K	

Modicon M340 Automation platform

Discrete I/O modules



Type of module			Mixed input/relay output modules	
			24 VDC inputs	24 VDC or 24...240 VAC relay outputs
Number of I/O			8	8
Connection			Screw or spring-type 20-way removable terminal block	
Nominal values	Inputs	Voltage	24 VDC (positive logic)	
		Current	3.5 mA	
	Outputs	DC voltage		24 VDC
		DC		2 (resistive load)
		AC voltage		220 VAC, Cosφ = 1
		AC		2 A
Input limit values	At state 1	Voltage	≥11V	
		Current	≥2 mA (for U ≥ 11 V)	
	At state 0	Voltage	5 V	
		Current	≤1.5 mA	
	Sensor power supply (ripple included)		19...30 V (possible up to 30 V, limited to 1 hour in every 24 hours)	
	Maximum dissipated power			3.1 W
Reference			BMX DDM 16025	

Connection accessories



20-way removable connection blocks			
For module with 20-way removable terminal block	Cage clamp	Screw clamp	Spring-type
References	BMX FTB 2000	BMX FTB 2010	BMX FTB 2020



Preformed cordsets for I/O modules with removable terminal block			
Preformed cordsets with one end with flying leads	One 20-way terminal block, one end with color-coded flying leads		
Length	3 m	5 m	10 m
References	BMX FTW 301	BMX FTW 501	BMX FTW 1001



Preformed cordsets for I/O modules with 40-way connectors					
Preformed cordsets		one end with flying leads		for Advantys Telefast ABE7 sub-bases	
No. of sheaths		1 x 20 wires (16 channels)	1 x 20 wires (32 channels)	1 x 20 wires (16 channels)	1 x 20 wires (32 channels)
Composition		One 40-way connector			
		1 end w. col-coded flying leads	2 ends w. col-coded flying leads	1 HE 10 connector	2 HE 10 connectors
Cross-section		0.324 mm ²			
Reference	L = 0.5 m	—	—	BMX FCC 051	BMX FCC 053
	L = 1 m	—	—	BMX FCC 101	BMX FCC 103
	L = 2 m	—	—	BMX FCC 201	BMX FCC 203
	L = 3 m	BMX FCW 301	BMX FCW 303	BMX FCC 301	BMX FCC 303
	L = 5 m	BMX FCW 501	BMX FCW 503	BMX FCC 501	BMX FCC 503
	L = 10 m	BMX FCW 1001	BMX FCW 1003	BMX FCC 1001	BMX FCC 1003

Modicon M340 Automation platform

Analog I/O modules



Type of module	Analog input module		
Input type	Isolated high-level inputs	Isolated inputs, low-level voltage, resistors, temperature probes, thermocouples	
Number of channels	4	4	8
Nature of inputs	$\pm 10\text{ V}$, $0\ldots 10\text{ V}$, $0\ldots 5\text{ V}$, $1\ldots 5\text{ V}$, $\pm 5\text{ V}$	$\pm 40\text{ mV}$, $\pm 80\text{ mV}$, $\pm 160\text{ mV}$, $\pm 320\text{ mV}$, $\pm 640\text{ mV}$, $\pm 1.28\text{ V}$	
Resolution	0.35 mV	15 mV + sign	
Reference	BMX AMI 0410	BMX ART 0414	BMX ART 0814



Type of module	Analog output module	
Output type	Isolated high-level outputs	
Number of channels	2	
Range	Voltage	$\pm 10\text{ V}$
	Current	$0\ldots 20\text{ mA}$ and $4\ldots 20\text{ mA}$
Resolution	15 bits + sign	
Reference	BMX AMO 0210	

Type of module		Mixed analog I/O module	
Channel type		Non-isolated high-level inputs	Non-isolated high-level outputs
Number of channels		4	2
Ranges		±10 V, 0...5 V, 0...10 V, 1...5 V, 0...20 mA, 4...20 mA	±10 V, 0...20 mA, 4...20 mA
Maximum conversion value	Voltage	± 11.25 V	± 11.25 V
	Current	0...30	0...24 mA
Resolution		14 bits, 12 bits, 13 bits, 12 bits	12 bits, 11 bits
Reference		BMX AMM 0600	

Counter modules



Type of module	Counter module		
	32 bits	16 bits	32 bits
Modularity	2 channels	8 channels	4 channels
No. of sensor inputs	6 per channel	2 per channel	3 per channel
No. of actuator outputs	2 per channel		
Module cycle time	1 ms	5 ms	
Applications	Upcounting, downcounting, measurement, frequency meter, frequency generator, axis following	Upcounting, downcounting, measurement, interfacing	
References	BMX EHC 0200	BMX EHC 0800	

Modicon M340 Automation platform

Connection accessories



20-way removable terminal blocks

For use with modules	BMX AMI 0410 - BMX AM0 0210 - BMX AMM 0600		
Composition	Cage clamp	Screw clamp	Spring-type
Reference	BMX FTB 2000	BMX FTB 2010	BMX FTB 2020



Preformed cordsets with one end with flying leads

For use with modules	BMX AMI 0410	BMX AM0 0210	BMX AMM 0600	BMX ART 0414	BMX ART 0814
Composition	One 20-way terminal block		1 end w. col-coded flying leads	One 40-way connector	1 end w. col-coded flying leads
Reference	L = 3 m	BMX FTW 301S		BMX FCW 301S	
	L = 5 m	BMX FTW 501S		BMX FCW 501S	

Advantys Telefast ABE 7 sub-bases

For use with modules	BMX AMI 0410	BMX ART 0414	BMX ART 0814
Composition	Distribution of isolated power supplies Delivers 4 protected isolated power supplies for 4...20 mA inputs. Direct connection of 4 inputs	Connection and provision of cold junction compensation for thermocouples Direct connection of 4 inputs	
Reference	ABE 7CPA410	ABE 7CPA412	



Preformed cordsets for Advantys Telefast ABE 7 sub-bases

For use with modules	BMX AMI 0410	BMX ART 0414	BMX ART 0814
Composition	One 20-way removable terminal block and one 25-way SUB-D connector for ABE 7CPA410 sub-base	One 40-way connector and one 25-way SUB-D connector for ABE 7CPA412 sub-base	
Reference	L = 1.5 m	BMX FCA150	BMX FCA152
	L = 3 m	BMX FCA300	BMX FCA302
	L = 5 m	BMX FCA500	BMX FCA502

Pack of connectors

For BMX EHC 0200 modules	Two 16-way connectors and one 10-way connector
Reference	BMX XTS HSC 20



20-way removable terminal blocks

For BMX EHC 0800 modules

Composition	Cage clamp	Screw clamp	Spring-type
References	BMX FTB 2000	BMX FTB 2010	BMX FTB 2020

Modicon Premium Automation platform

Processors under Unity Pro software



Type of processor		TSX 5710 4 racks max.	TSX 5720 16 racks max.	TSX 5730 16 racks max.
Number of I/O in racks	Discrete	512	1024	1024
	Analog	24	80	128
Integrated process control		No / Yes	30 loops / Yes	45 loops / Yes
Application-specific channels (counter, position control, weighing)		8	24	32
Bus	AS-Interface cabling system	2	4	8
	CANopen machine bus	1	1	1
	INTERBUS, Profibus DP fieldbus	–	1	3
Networks (Ethernet, Modbus Plus, Fipway)		1	2	3
Memory capacity	Without PCMCIA extension	96 Kb data/prog.	160/192 Kb data/prog. (1)	192/208 Kb data/prog. (1)
	With PCMCIA extension	96 Kb data/224 Kb prog.	160/192 Kb data (1)/768 Kb prog.	192/208 Kb data (1)/1,75 MB prog.
Execution time for one instruction without ext. PCMCIA	Boolean	0.19 µs	0.19 µs	0.12 µs
	On word or arithmetic	0.25 µs	0.25 µs	0.17 µs
Reference	Without integrated port	TSXP57104M (6)	TSXP57204M (6)	TSXP57304M (6)
	Integrated Ethernet	TSXP571634M (2) (6)	TSXP572634M (6)	TSXP573634M (6)
	Integrated CANopen	–	–	–
	Integrated Fipio	TSXP57154M (6)	TSXP57254M (6)	TSXP57354M (6)

Processors under PL7 software



Type of processor		TSX 5710 4 racks max.	TSX 5720 16 racks max.	TSX 5730 16 racks max.
Number of I/O in racks	Discrete	512	1024	1024
	Analog	24	80	128
Integrated process control		No	30 loops	45 loops
Application-specific channels (counter, position control, weighing)		8	24	32
Bus	AS-Interface cabling system	2	4	8
	CANopen machine bus	1 (with TSXP57103M)	1	1
	INTERBUS, Profibus DP fieldbus	–	1	2
Networks (Ethernet, Modbus Plus, Fipway)		1	1	3
Memory capacity	Without PCMCIA extension	32 K words data/prog.	48 K words data/prog. (4)	64/80 K words data/prog. (4)
	With PCMCIA extension	32 K words data/64 K words prog.	32 K words data (4)/160 K words prog.	80/96 K words data (4)/384 K words prog.
Execution time for one instruction without ext. PCMCIA	Boolean	0.19 µs	0.19 µs	0.12 µs
	On word or arithmetic	0.25 µs	0.25 µs	0.17 µs
Reference	Without integrated port	TSXP57103M (6)	TSXP57203M (6)	TSXP57303AM (6)
	Integrated Ethernet	–	TSXP572623M (6)	TSXP573623AM (6)
	Integrated Fipio	TSXP57153M (6)	TSXP57253M (6)	TSXP57353AM (6)
	Integrated Ethernet and Fipio	–	TSXP572823M (6)	–

(1) The second value corresponds to the integrated memory capacity when the processor is equipped with a Fipio manager integrated link

(2) Processor with double format

(3) PC format card on PCI bus

(4) The second value corresponds to the processor with integrated Fipio bus manager link.

(5) with PL7 V4.4 min.

(6) For coated version add C at the end of the reference: example **TSXP571634M** becomes **TSXP571634MC**



TSX 5740 16 racks max.	TSX 5750 16 racks max.	TSX 5760	TSXH5724M	TSXH5744M
2040	2040	2048	1024	2048
256	512	512	80	256
60 loops / Yes	90 loops / Yes	90 loops / Yes	30 loops / Yes	60 loops / Yes
64	64	64	0	0
8	8	8	0	0
1	1	1	0	0
4	5	5	0	0
4	4	4	2	4
320 Kb data/prog.	1024 Kb data/prog.	2048 Kb data/prog.	192 Kb	440 Kb
440 Kb data/2 MB prog.	1024 Kb data/7 MB prog.	2048 Kb data/7 MB prog.	192 Kb data/768 Kb prog.	440 Ko data/2 MB prog.
0.06 µs	0.037 µs	0,037 µs	0,039 µs	0,039 µs
0.07 µs	0.045 µs	0,045 µs	0,054 µs	0,054 µs
–	–	–	TSXH5724M (6)	TSXH5744M (6)
TSXP574634M (6)	TSXP575634M (6)	TSXP576634M (6)		
–	–	–		
TSXP57454M (6)	TSXP57554M (6)	–		

Atrium slot-PLCs under Unity Pro software



TSX 5740 16 racks max.	PCI 5720 16 racks max.	PCI 5730 16 racks max.
2048	1024	1024
256	80	128
60 loops	30 loops / Yes	45 loops / Yes
64	24	32
8	4	8
1	1	1
2	1	3
4	3 (6)	4
96 K words data/prog.	160 Kb data/prog. (1)	208 Kb data/prog. (1)
176 K words data/992 K words prog. (5)	160 Kb data/768 Kb prog.	208 Kb data (1)/1,75 MB prog.
0.06 µs	0.19 µs	0.12 µs
0.08 µs	0.25 µs	0.17 µs
–	TSXPCI57204M (3)	–
–	–	–
TSXP57453AM (6)	–	–
TSXP574823AM (6)	–	TSXPCI57354M (3)

Modicon Premium Automation platform

Memory extensions for Unity Pro processors



Type of PCMCIA card		Application		Additional data
Technology		SRAM	Flash EPROM only	SRAM
Memory size	96 Kb	—	TSXMFPPB096K (3)	—
	128 Kb	TSXMRPP128K	TSXMFPP128K	—
	224 Kb	TSXMRPP224K / TSXMCPC224K	TSXMFPP224K	—
	384 Kb	TSXMRPP384K	TSXMFPP384K	—
	448 Kb	TSXMRPC448K (1)	—	—
	512 Kb	—	TSXMCPC512K (2) / TSXMFPP512K	—
	768 Kb	TSXMRPC768K (1)	—	—
	1 MB	TSXMRPC001M (1) (6)	TSXMFPP001M	—
	1.7 MB	TSXMRPC01M7	—	—
	2 MB	TSXMRPC002M (1)	TSXMCPC002M (2) / TSXMFPPC002M	—
	3 MB	TSXMRPC003M (1) (6)	—	—
	4 MB	—	TSXMFPP004M	TSXMRPF004M
	7 MB	TSXMRPC007M (1) (6)	—	—
	8 MB	—	—	TSXMRPF008M

(1) By configuration, the user can reserve part of the memory space for data storage (recipes, production data) on request.

(2) These cards have an additional SRAM area for storing data (recipes, production data).

(3) Backup cartridge of the program when this one reside entirely in PLC internal memory.

Memory extensions for PL7 processors



Type of PCMCIA card		Application		Additional data
Technology		SRAM	Flash EPROM only	SRAM
Memory size (4)	32 K words	TSXMRPP128K	TSXMFPP128K	—
	64 K words	TSXMRPP224K	TSXMFPP224K	—
	64 K words/128 K words	TSXMRPP384K	TSXMCPC224K	—
	96 K words	—	TSXMFPPB096K	—
	128 K words	TSXMRPC448K	TSXMFPP384K	—
	128 K words/128 K words	TSXMRPC768K (5)	—	—
	256 K words	TSXMRPC001M (6)	—	—
	256 K words/640 K words	TSXMRPC01M7 (5)	—	—
	384 K words/640 K words	TSXMRPC002M	—	—
	512 K words	TSXMRPC003M (5) (6)	—	—
	992 K words/640 K words	TSXMRPC007M (6)	—	—
	2048 K words	—	—	TSXMRPF004M

(4) The 1st value corresponds to the size of the application area, the second to the size of the additional data area for storing data (recipes, production data, etc).

(5) These cards have an additional SRAM area for storing application object symbols.

(6) For coated version add C at the end of the reference: example **TSXMRPC001M** becomes **TSXMRPC001MC**

Power supply modules ⁽¹⁾



Type of power supply module for	Premium					Atrium (2)
Input voltage	24 VDC		100...240 VAC	100...120/200...240 VAC		24 VDC
Output voltage	5 VDC/24 VDC					5 VDC
Total useful power	26 W	50 W	26 W	50 W	77 W	26 W
Format	Standard	Double	Standard	Double	Double	–
Reference	TSXPSY1610M (4)	TSXPSY3610M (4)	TSXPSY2600M (4)	TSXPSY5500M (4)	TSXPSY8500M (4)	TSXPSI2010

(1) Process power supplies see chapter 6 “Power supply”

(2) Only for Atrium slot-PLCs under Unity

Racks



Type of rack			Non extendable	Extendable
For configuration			Mono-rack	Multi-rack (16 max.)
Dimensions WxDxP				
Reference	4 positions	188 x 160 x 151,5 mm ⁽³⁾	–	TSXRKY4EX ⁽⁴⁾
	6 positions	261,6 x 160 x 151,5 mm ⁽³⁾	TSXRKY6 ⁽⁴⁾	TSXRKY6EX ⁽⁴⁾
	8 positions	335,3 x 160 x 151,5 mm ⁽³⁾	TSXRKY8 ⁽⁴⁾	TSXRKY8EX ⁽⁴⁾
	12 positions	482,6 x 160 x 151,5 mm ⁽³⁾	TSXRKY12 ⁽⁴⁾	TSXRKY12EX ⁽⁴⁾

(3) Height of I/O modules : 151,5 mm with HE 10 or SUB-D connectors, 165 mm with screw terminals

(4) For coated version add C at the end of the reference: example **TSXPSY1610M** becomes **TSXPSY1610MC**

Connection accessories

Type	Bus X daisy chaining cable for extendable racks	Line terminators
Reference	–	Set of 2
	–	TSXTLYEX
	L = 1 m	TSXCBY010K
	L = 3 m	TSXCBY030K
	L = 5 m	TSXCBY050K
	L = 12 m	TSXCBY120K
	L = 18 m	TSXCBY180K
	L = 28 m	TSXCBY280K
	L = 38 m	TSXCBY380K
	L = 50 m	TSXCBY500K
	L = 72 m	TSXCBY720K
	L = 100 m	TSXCBY1000K

Modicon Premium Automation platform

Discrete I/O modules



Type of module		Discrete inputs				
Connection		By screw terminals TSXBLY01 (1)		By HE 10 connector (2) high density		
Number of isolated channels		8	16	16 (3)	32	64
Input voltage	24 VDC	TSXDEY08D2 (5)	TSXDEY16D2 (5)	TSXDEY16FK (5)	TSXDEY32D2K (5)	TSXDEY64D2K (5)
	48 VDC	–	TSXDEY16D3 (5)	–	TSXDEY32D3K (5)	–
	24 VAC	–	TSXDEY16A2 (4) (5)	–	–	–
	48 VAC	–	TSXDEY16A3 (5)	–	–	–
	100...120 VAC	–	TSXDEY16A4 (5)	–	–	–
	200...240 VAC	–	TSXDEY16A5 (5)	–	–	–

(1) Terminal block to be ordered separately

(2) For use with Advantys Telefast ABE7 wiring system

(3) Module with high-speed isolated inputs (filtering from 0.1 to 7.5 ms) able to activate the event-triggered task

(4) Module also compatible with 24 VDC negative logic



Type of module		Discrete outputs							
		Solid state				Relay		Triac	
Connection		By screw terminals TSXBLY01 (1)		By HE10 conn. (2)		By screw terminals TSXBLY01 (1)			
Number of protected channels		8	16	32	64	8	16	8	16
Output voltage/current 24 VDC/0,5 A		TSXDSY08T2 (5)	TSXDSY16T2 (5)	–	–	–	–	–	–
	24 VDC/2 A	TSXDSY08T2 (5)	–	–	–	–	–	–	–
	24 VDC/0.1 A	–	–	TSXDSY32T2K (5)	TSXDSY64T2K (5)	–	–	–	–
	48 VDC/1 A	TSXDSY08T31 (5)	–	–	–	–	–	–	–
	48 VDC/0.25 A	–	TSXDSY16T3 (5)	–	–	–	–	–	–
	24...48 VDC-24...240 VAC/5 A Th.c	–	–	–	–	TSXDSY08R5A (5)	–	–	–
	24...120 VAC/5 A Th.c	–	–	–	–	TSXDSY08R4D (5)	–	–	–
	24...120 VAC/1 A	–	–	–	–	–	–	–	TSXDSY16S4 (5)
	48...240 VAC/1 A	–	–	–	–	–	–	–	TSXDSY16S5
	48...240 VA /2 A	–	–	–	–	–	–	TSXDSY08S5	–
	24 VDC-24...240 VAC/3A	–	–	–	–	TSXDSY08R5 (5)	TSXDSY16R5 (5)	–	–

(1) Terminal block to be ordered separately

(2) For use with Advantys Telefast ABE7 wiring system



Type of module		Discrete I/O	
Connection		By HE 10 connector (2) high density	
Number of inputs		16 high-speed	
Number of protected outputs		12 solid state	12 reflex or timed
Output voltage/current	24 VDC/0.5 A	TSXDMY28FK (5)	TSXDMY28RFX (5)

(2) For use with Advantys Telefast ABE7 wiring system

(5) For coated version add C at the end of the reference: example TSXDEY08D2 becomes TSXDEY08D2C

Connection accessories: See www.schneider-electric.com

Analog I/O modules



Type of module		Analog input					
		High level with common point			High level isolated	Low level isolated	
Connection		By 25-way SUB-D connector					By terminal block (1)
Number of channels		4 high-speed	8	16	8	16	4
Resolution		16 bits	12 bits		16 bits	16 bits	16 bits
Isolation	Between channels	Common point	Common point	Common point	± 200 VDC	± 100 VDC	± 2830 Vrms
	Between channels and earth	~ 1000 Vrms	~ 1000 Vrms	~ 1000 Vrms	~ 1000 Vrms	~ 1000 Vrms	~ 1780 Vrms
Reference	High level input (2)	TSXAEY420 (7)	TSXAEY800 (7)	TSYAEY1600 (7)	TSXAEY810 (7)	–	–
	Multi-range	–	–	–	–	TSXAEY1614 (3)(7)	TSXAEY414 (4) (7)

(1) Screw terminals **TSXBLY01** to be ordered separately

(2) ± 10 V, 0...10 V, 0...5 V, 1...5 V, 0...20 mA, 4...20 mA

(3) ± 63 mV thermocouple (B, E, J, K, L, N, R, S, T, U)

(4) ± 10 V, ± 5 V, 0...10 V, 0...5 V, 1...5 V, 0...20 mA, 4...20 mA, -13...+63 mV, 0...400 W, 0...3850 W, thermal probe, thermocouple



Type of module		Analog output	
		Isolated	With common point
Connection		By screw terminals TSXBLY01 (5)	By 25-way SUB-D connector
Number of channels		4	8
Resolution		11 bits + sign	13 bits + sign
Isolation	Between channels	~ 1500 Vrms	Common point
	Between channels and earth	~ 1500 Vrms	~ 1000 Vrms
Reference	Input signal (6)	TSXASY410 (7)	TSXASY800 (7)

(5) Terminal block to be ordered separately

(6) ± 10 V, 0...10 V, 0...20 mA, 4...20 mA.

(7) For coated version add C at the end of the reference: example **TSXAEY420** becomes **TSXAEY420C**

Modicon Premium Automation platform

Counter modules



Type of module	Counter		Counter/measurement	Electronic cam
Type of inputs for	Sensors (2) Incremental encoders (3)		Sensors (2) Encoders (3)(4)	Incremental encoders (3) Absolute encoders (5)
Counting	40 kHz		500 kHz/200 kHz (5)	
Cycle time module	5 ms	10 ms	1 ms	–
Number of channels	2	4	2	128 cams
Number of axes	–	–	–	1
Reference	TSXCTY2A (1)	TSXCTY4A (1)	TSXCTY2C (1)	TSXCCY1128 (1)

(1) For coated version add **C** at the end of the reference: example TSXCTY2A becomes TSXCTY2AC

(2) For 2/3-wire PNP/NPN 24 VDC sensors

(3) For 5 VDC RS422, 10...30 VDC Totem Pole incremental encoders

(4) For SSI serial or parallel output absolute encoders

(5) For RS485 serial or parallel output absolute encoders

Motion control modules



Module type	For translators (amplifier for stepper motor)		For analog control servomotors (for asynchronous and brushless motors)			
Control outputs	RS 422		+/- 10 V			
Compatible with drives	Lexium 05, Twin Line		Lexium 05 / 15 LP, MP and HP, Twin Line			
Functions	Linear axes	–	Limited	Limited or infinite	Limited or infinite(6)	
	Slave axes	–	With static ratio	With dynamic ratio	–	
Frequency for each axis	187 kHz		500 kHz with incremental encoder, 200 kHz with absolute encoder (7)			
Number of axes	1	2	2	4	2	3
Reference	TSXCFY11 (1)	TSXCFY21 (1)	TSXCAY21 (1)	TSXCAY41 (1)	TSXCAY22 (1)	TSXCAY42 (1)
					TSXCAY33 (1)	

(6) With linear interpolation on 2 or 3 axes

(7) SSI serial or with parallel outputs



Module type	Servomotors with SERCOS® digital ring (for brushless motors)		
Control outputs	SERCOS® network ring		
Compatible with ranges	Lexium 15 LP, MP and HP		
Functions	Linear or infinite independent axes, slave axes with cam profile or ratio		
Processing	4 sets of axes with linear interpolation from 2 to 8 axes	4 sets of axes with linear and circular interpolation from 2 to 3 axes (8)	4 sets of axes with linear interpolation from 2 to 8 axes
Frequency for each axis	4 MB SERCOS® network ring		
Number of axes	8 (9)	8 (9)	16 (10)
Reference	TSXCSY84	TSXCSY85	TSXCSY164


(8) TSXCSY85 module supplied with TJE trajectory editor: linear trajectories with links between segments according to polynomial or circular interpolation and circular trajectories.

(9) 8 real axes, 4 imaginary axes and 4 remote axes

(10) 16 axes (real axes, imaginary and remote axes)

Weighing modules



Type of module	ISP Plus supplied uncalibrated		supplied calibrated and  offer
Load cell inputs / outputs	50 measurements (for 1 to 8 load cells) / 2 discrete and 1 RS 485 for display unit		
Reference	Without display unit	TSXISPY101 (1)	Please consult your Schneider-electric agency
	With display unit TSXXBTN410	TSXISPY121	Please consult your Schneider-electric agency

Connection accessories: See www.schneider-electric.com

Communication modules

Transparent
Ready



Type of module		Ethernet TCP/IP				
Speed		10 MBps	10/100 MBps			
Standard services		Ethway, TCP/IP (Uni-TE, Modbus)	TCP/IP (Uni-TE, Modbus)			
Transparent Ready	Classe	C10	B30	B30	C30	D10
	Global Data	–	Yes	Yes	Yes	–
	I/O Scanning	–	Yes	Yes	Yes	–
	TCP Open	Yes	–	–	Yes	–
Web server	Standard services	Yes	Yes	Yes	Yes	Yes
	FactoryCast services	Yes	–	–	Yes	–
	FactoryCast HMI services	–	–	–	–	Yes
Reference		TSXEY110WS (4)	TSXP57 (1)	TSXEY4103 (4)	TSXEY5103 (4)	TSXWY100 (4)

(1) References: see pages 3/18 and 3/19, Premium processors with integrated Ethernet TCP/IP port



Type of module	AS-Interface cabling system	CANopen machine bus	Fipio manager fieldbus	INTERBUS fieldbus	Profibus DP fieldbus
Name and description	In-rack	PCMCIA	Integrated port	In-rack	In-rack
Speed	167 kBps	20 K...1 MBps	1 MBps	0.5 MBps	9.6 K...12 MBps
Reference	TSXSAY1000 (4)	TSXCPP110 (4)	TSXP57 (2)	TSXIBY100 (4)	TSXPBY100

(2) References: see pages 3/18 and 3/19, Premium processors with integrated Fipio port



Type of module			Serial links			
			Uni-Telway		Modbus	ASCII
Name and description			Integrated port	In-rack	PCMCIA	PCMCIA
Speed			19.2 kBps	19.2 kBps	1.2...19.2 kBps	1.2...19.2 kBps
Reference	With interface	RS 485	TSXP57 (1)	TSXSCY21601 (2) (4)	TSXSACP114 (4)	TSXSACP114 (4)
		RS 232D	–	–	TSXSACP111 (4)	TSXSACP111 (4)
		20mA CL	–	–	TSXSACP112 (4)	TSXSACP112 (4)

(1) References: see pages 3/18 and 3/19, Premium processors with integrated Ethernet TCP/IP port

(2) Also designed for Modbus serial (channel 0).



Type of module	Other networks		
	Modbus Plus	Fipway	Fipio (agent function)
Name and description	PCMCIA card	PCMCIA card	PCMCIA card
Speed	1 MBps	1 MBps	1 MBps
Reference	TSXMBP100 (4)	TSXFPP20 (4)	TSXFPP10 (4)

(4) For coated version add C at the end of the reference: example TSXEY110WS becomes TSXEY110WSC

Modicon Quantum Automation platform

Processors under Unity Pro software



Type of processor		Simple applications	Simple and medium complexity applications
Max. number of discrete I/O (1)	Local	Unlimited (27 slots max.)	
	Remote/distributed	31744 inputs (RIO)/8000 inputs (DIO) and 31744 outputs (RIO)/8000 outputs (DIO)	
Max. number of analog I/O (1)	Local	Unlimited (27 slots max.)	
	Remote/distributed	1984 inputs (RIO)/500 inputs (DIO) and 1984 outputs (RIO)/500 outputs (DIO)	
Type of application-specific I/O		Intrinsically safe I/O, counter, motion control, high-speed interrupt inputs, time-stamp, serial link, AS-Interface sensor/actuator bus	
Communication ports (2)	Integrated Modbus	2 RS 232/RS 485	2 RS 232
	Modbus Plus	1 integrated, 2 in local rack	1 integrated, 6 in local rack
	Ethernet TCP/IP	2 in local rack	6 in local rack
	Fieldbus	Profibus DP: 2 in local rack	Profibus DP: 6 in local rack
Memory capacity	Integrated	2 MB	2 MB
	With PCMCIA extension	—	—
	Data storage	—	—
Reference		140CPU31110 (4)	140CPU43412U (4)

Processors under Concept/ProWORX software



Type of processor		Simple applications	
Max. number of discrete I/O (1)	Local	1024 (27 slots max.)	
	Decentralized/distributed	31744 inputs (RIO)/8000 inputs (DIO) and 31744 outputs (RIO)/8000 outputs (DIO)	
Max. number of analog I/O (1)	Local	Unlimited (27 slots max.)	
	Decentralized/distributed	1984 inputs (RIO)/500 inputs (DIO) and 1984 outputs (RIO)/500 outputs (DIO)	
Type of application-specific I/O		Intrinsically safe I/O, counter, motion control, high-speed interrupt inputs, time-stamp, serial link, AS-Interface sensor/actuator bus	
Communication ports (2)	Integrated Modbus	1 RS 232	
	Modbus Plus	1 integrated, 2 in local rack	
	Ethernet TCP/IP	2 in local rack	
	Fieldbus	INTERBUS/Profibus DP: 2 in local rack	
Memory capacity	Integrated	256 Kb	512 Kb
Reference	Concept/ProWORX	140CPU11302 (4)	140CPU11303 (4)

(1) The maximum values for the number of discrete or analog I/O are not cumulative

(2) The numbers of communication modules are not cumulative, 2 or 6 in local rack, depending on model

(3) Processor compatible with Unity Pro software after updating its firmware (via OS-Loader included in Unity Pro)

(4) For coated version add C at the end of the reference: example **T140CPU31110** becomes **140CPU31110C**



	Complex applications			Hot Standby redundant applications		
	Unlimited (26 slots max.)			Unlimited (13 slots max.)	Unlimited (26 slots max.)	Unlimited (13 slots max.)
	31744 inputs (RIO)/8000 inputs (DIO) and 31744 outputs (RIO)/8000 outputs (DIO)			31744 inputs and 31744 outputs	31744 inputs (RIO)/8000 inputs (DIO) and 31744 outputs (RIO)/8000 outputs (DIO)	31744 inputs and 31744 outputs
	Unlimited (27 slots max.)			Unlimited (13 slots max.)	Unlimited (27 slots max.)	Unlimited (13 slots max.)
	1984 inputs (RIO)/500 inputs (DIO) and 1984 outputs (RIO)/500 outputs (DIO)			1984 inputs and 1984 outputs	1984 inputs (RIO)/500 inputs (DIO) and 1984 outputs (RIO)/500 outputs (DIO)	1984 inputs and 1984 outputs
	Intrinsically safe I/O, counter, motion control, high-speed interrupt inputs, time-stamp, serial link, AS-Interface sensor/actuator bus			–		–
	1 RS 232/485			1 RS 232/485	1 RS 232/485	1 RS 232/485
	1 integrated, 6 in local rack			1 integrated	1 integrated, 6 in local rack	1 integrated
	1 integrated, 6 in local rack			1 integrated, 6 in local rack	6 in local rack	1 integrated, 6 in local rack
	Profibus DP: 6 in local rack			–	Profibus DP: 6 in local rack	–
	2 MB	4 MB		2 MB	2 MB	2 MB
	7 MB			7 MB	7 MB	7 MB
	8 MB			–	8 MB	–
	140CPU65150 (4)	140CPU65160 (4)	140CPU65260 (4)	140CPU65160S	140CPU67160 (4)	140CPU67160S



Simple and medium complexity applications		Complex applications
1024 (27 slots max.)		
31744 inputs (RIO)/8000 inputs (DIO) and 31744 outputs (RIO)/8000 outputs (DIO)		
Unlimited (27 slots max.)		
1984 inputs (RIO)/500 inputs (DIO) and 1984 outputs (RIO)/500 outputs (DIO)		
Intrinsically safe I/O, counter, motion control, high-speed interrupt inputs, time-stamp, serial link, AS-Interface sensor/actuator bus		
2 RS 232		
1 integrated, 6 in local rack		
6 in local rack		
INTERBUS/Profibus DP: 6 in local rack		
2 MB		4 MB
140CPU43412A (3) (4)		140CPU53414B (3) (4)

Modicon Quantum Automation platform

Power supply modules ⁽¹⁾



Type of power supply module for			Quantum				
Input voltage			24 VDC	48...60 VDC	100...150 VDC	120...230 VAC	115/230 VAC
Output current			8 A/3 A (5)	8 A	8 A/3 A	8 A/3 A (1)	11 A
Reference	Type	Standalone (2)	140CPS21100 (6)	–	140CPS51100 (6)	140CPS11100 (6)	–
		Summable	140CPS21400 (6)	140CPS41400 (6)	–	–	140CPS11420 (6)
		Redundant	140CPS22400 (6)	140CPS42400 (6)	140CPS52400 (6)	140CPS12400 (6)	140CPS12420 (6)

(1) Process power supplies see chapter 6 "Power supply"

(2) The output current for the standalone power supply modules is 3 A

PCMCIA memory extensions



Type of PCMCIA card for Unity processors 140CPU65/67		Application		Additional data
Technology		SRAM	Flash EPROM	SRAM
Memory size	512 Kb/512 Kb (4)	–	TSXMCPC512K (3)	–
	1 MB (5)	TSXMRPC001M (6)	TSXMFPP001M	–
	2 MB (5)	TSXMRPC002M	TSXMFPP002M	–
	2 MB/1 MB (4)	–	TSXMCPC002M	–
	3 MB (5)	TSXMRPC003M (6)	–	–
	4 MB	–	TSXMFPP004M	TSXMRPF004M
	7 MB (5)	TSXMRPC007M (6)	–	–
	8 MB	–	–	TSXMRPF008M

(3) These cards have an additional SRAM area for storing data (recipes, production data).

(4) The 1st value corresponds to the size of the application area, the second to the size of the additional data area for storing data (recipes, production data, etc)

(5) By configuration the user can reserve part of the memory space for data storage (recipes, production data, etc)

(6) For coated version add C at the end of the reference: example **TSXMRPC001M** becomes **TSXMRPC001MC**

Racks



Type			Racks
		Dimensions WxDxH	
References	2 slots	104x104x290 mm	140XBP00200 (2)
	3 slots	143x104x290 mm	140XBP00300 (2)
	4 slots	184x104x290 mm	140XBP00400 (2)
	6 slots	265x104x290 mm	140XBP00600 (2)
	10 slots	428x104x290 mm	140XBP01000 (2)
	16 slots	671x104x290 mm	140XBP01600 (2)
	Rack extension module		140XBE10000 (2)

(1) Local extension module, to be placed in main rack and secondary rack.

(2) For coated version add C at the end of the reference: example **140XBP00200** becomes **140XBP00200C**

Connection accessories ⁽³⁾

Type		Cable for extension racks (main and secondary)
References	L = 1 m	140XCA71703
	L = 2 m	140XCA71706
	L = 3 m	140XCA71709

(3) **Other accessories:** See www.schneider-electric.com

Modicon Quantum Automation platform

Discrete I/O modules



Type of module (4)		Discrete inputs					
Connection		By screw terminals 140XTS00200 (to be ordered separately)					
Number of isolated channels		16	4 groups of 8	3 groups of 8	2 groups of 8	6 groups of 16	8 groups of 2
Input voltage	5 VDC TTL (negative logic)	—	140DDI15310	—	—	—	—
	24 VDC	—	140DDI35300(1)	—	—	140DDI36400	—
	10...60 VDC	—	140DDI85300	—	—	—	140DDI84100
	20...30 VDC	—	140DSI35300(1)	—	—	—	—
	125 VDC	—	—	140DDI67300	—	—	—
	24 VAC	140DAI34000	140DAI35300	—	—	—	—
	48 VAC	140DAI44000	140DAI45300	—	—	—	—
	115 VAC	140DAI54000	140DAI55300	—	140DAI54300	—	—
	230 VAC	140DAI74000	140DAI75300	—	—	—	—

(1) For negative logic, replace 00 at the end of the reference with 10, for example 140DDI35300 becomes 140DDI35310.



Type of module (4)		Discrete outputs					
		Solid state					
Connection		By screw terminals 140XTS00200 (to be ordered separately)					
Number of protected channels		16	4 groups of 8	4 groups of 4	2 groups of 8	6 groups of 16	2 groups of 6
Output voltage/current	5 VDC TTL/0.075 A (2)	—	140DDO15310	—	—	—	—
	24 VDC/0.5 A	—	140DDO35301(1)	—	—	—	—
	10...30 VDC/0.5 A (3)	—	140DVO85300	—	—	—	—
	19.2...30 VDC/0.5 A	—	—	—	—	140DDO36400	—
	10...60 VDC/2 A	—	—	—	140DDO84300	—	—
	24...125 VDC/0.75 A	—	—	—	—	—	140DDO88500
	24...48 VAC/4 A	—	—	140DAO84220	—	—	—
	24...115 VAC/4 A	140DAO84010	—	—	—	—	—
	24...230 VAC/ 4-3 A	140DAO84000	140DAO85300	—	—	—	—
	100...230 VAC/4-3 A	—	—	140DAO84210	—	—	—

(1) For negative logic, replace 01 at the end of the reference with 10, for example 140DDO35301 becomes 140DDO35310.

(2) Negative logic

(3) Controlled outputs



Type of module (4)		Discrete I/O			Discrete outputs	
		Solid state			Relay	
Connection		By screw terminals 140XTS00200 (to be ordered separately)			—	
Number of I/O		2 groups of 8/2 groups of 4		1 group of 4/ 4 isolated	—/16 NO	—/8 NO/NC
Input voltage		24 VDC	125 VAC	125 VDC	—	—
Output voltage/current		30 VDC/15 A	125 VAC/4 A	125 VDC/4 A	150 VDC or 250 VAC/2 A	150 VDC or 250 VAC/5 A
Reference		140DDM39000	140DAM59000	140DDM69000	140DRA84000	140DRC83000

(4) For coated version add C at the end of the reference: example 140DDI15310 becomes 140DDI15310 C

Analog I/O modules



Type of module (3)	Analog inputs				
Connection	By screw terminals 140XTS00200 (to be ordered separately)				
Number of channels	8	16	8		
Input signal	4...20 mA 1...5 V	0...25/20 mA 4...20 mA	(1)	Thermal probe Pt, Ni	Thermocouple (2)
Resolution	12 bits	0...25000 points	16 bits	12 bits + sign	16 bits
Reference	140ACI03000	140ACI04000	140AVI03000	140ARI03010	140ATI03000

(1) 0...25 mA, ± 20 mA, 4...20 mA, 0...10 V, ± 10 V, 0...5 V, ± 5 V, 1...5 V.

(2) Type B, E, J, K, R, S, T, mV



Type of module (3)	Analog output		
Connection	By screw terminals 140XTS00200 (to be ordered separately)		
Number of channels	4	8	4
Input signal	4...20 mA	0...25/20 mA 4...20 mA	0...10 V, ± 10 V 0...5 V, ± 5 V
Resolution	12 bits	0...25000 points	12 bits
Reference	140ACO02000	140ACO13000	140AVO02000




Type of module (3)	Analog I/O
Connection	By screw terminals 140XTS00200 (to be ordered separately)
Number of inputs	4
Number of outputs	2
Input signal	0...20 mA, ± 20 mA, 4...20 mA, 0...10 V, ± 10 V, 0...5 V, ± 5 V, 1...5 V.
Resolution	Inputs 16 bits, outputs 12 bits
Reference	140AMM09000

(3) For coated version add C at the end of the reference: example 140ACI03000 becomes 140ACI03000C

Modicon Quantum Automation platform

Intrinsically safe I/O modules



Type of module	I/O 		Analog		
	Discrete				
Connection	By screw terminal 140XTS33200 (to be ordered separately)				
Number of inputs	8	–	8	–	
Number of outputs	–	8	–	8	
Input signal	–	–	Thermal probe	0...25/20 mA	
			Thermocouple (1)	4...25 mA	
Resolution	–	–	12 bits + sign	0...25000 points	15 bits
Reference	140DII33000	140DIO33000	140AII33000	140AII33010	140AIO33000

(1) Type J, K, E, T, S, R, B, mV

Counter and special purpose modules



Type of module	High-speed counter		High-speed inputs with interrupt	Time-stamp system	
Type of inputs for	Incremental encoders		Discrete 24 VDC (2)	DCF 77	Discrete
				24 VDC (3)	24...125 VDC
Counting frequency	100 kHz	500 kHz	–	–	–
Number of channels	5	2	16	1	32
Reference	140EHC10500	140EHC20200	140HLI34000	140DCF07700	140ERT85410 (4)

(2) 3 operating modes: Interrupt, latch, high-speed inputs, on rising or falling edge.

(3) For GPS or DCF time receiver

(4) one input complying with DCF77 standard

Safety I/O modules



Type of modules	Analog	Discrete	
Connection	Screw terminal		
Number of inputs	8 analog inputs	16 discrete inputs	–
Number of outputs	–	–	16 discrete outputs
Input signal	4...20mA	24VDC	–
Output voltage	–	–	24VDC
Resolution	16 bits	–	–
Certification	Functional Safety SIL2, UL, CE, CSA, Haz-loc		
Reference	140SAI94000S	140SDI95300S	140SDO95300S

Communication modules

Transparent
Ready



Type of module		Ethernet TCP/IP network			
Speed		10/100 MBps			
Standard services		TCP/IP (Modbus)			
Transparent Ready	Class	B30	B30	C30	D10
	Global Data	Yes	Yes	Yes	–
	I/O Scanning	Yes	Yes	Yes	–
	FDR server	Yes	Yes	Yes	–
	SNMP protocol	Yes	Yes	Yes	Yes
Web server	Standard services	Yes	Yes	Yes	Yes
	FactoryCast services	–	–	Yes	Yes
	FactoryCast HMI services	–	–	–	Yes
Reference		140CPU651 (1)	140NOE77101	140NOE77111	140NWM10000

(1) References: see pages 3/26 and 3/27, Quantum processors with integrated Ethernet TCP/IP



Type of module	Modbus Plus network	AS-Interface cabling system	INTERBUS fieldbus	Profibus DP Master V1 fieldbus (2)
Name and description	Integrated link	In-rack	In-rack	In-rack
Speed	1 MBps	167 kBps	0,5 MBps	to 12 MBps
Reference	140CPU (3)	140EIA92100	140NOA62200	PTQ PDP MV1

(2) from your partner Prosoft, www.prosoft-technology.com

(3) References: see pages 3/26 and 3/27, Quantum processors with integrated Modbus Plus



Type of module	Serial link	
	Modbus	ASCII
Name and description	Integrated link	In-rack
Speed	19.2 kBps	19.2 kBps
Reference	140CPU (4) (5)	140ESI06210


(4) References: see pages 3/26 and 3/27, Quantum processors with integrated Modbus

(5) RS 232/RS 485 on 140CPU651●● and 140CPU67160 processors and RS 232 on 140CPU31110, 140CPU43412A, 140CPU53414A processors.

To operate in a corrosive environment, Quantum modules can be ordered with a conformal coating applied to components of the product. Conformal coating will extend its life and enhance its environmental performance capabilities. To order conformal coating append a C to the standard catalog number. For example, 140CPS 11420 > 140CPS 114 20C

Automation systems — Unity software

For Modicon M340, Premium, Quantum and Atrium



Software type		Unity Pro Small version 3.0			
License type version 3.0		Single (1 workstation)	Group (3 workstations)	Team (10 workstations)	Site (> 10 workstations)
References	Software pack	UNYSPUSFUCD30	UNYSPUSFGCD30	UNYSPUSFTCD30	–
	Update (1)	UNYSPUSZUCD30	UNYSPUSZGCD30	UNYSPUSZTCD30	–
Software type		Unity Pro Medium version 3.0			
License type version 3.0		Single (1 workstation)	Group (3 workstations)	Team (10 workstations)	Site (> 10 workstations)
References	Software pack	UNYSPUMFUCD30	UNYSPUMFGCD30	UNYSPUMFTCD30	–
	Update (2)	UNYSPUMZUCD30	UNYSPUMZGCD30	UNYSPUMZTCD30	–
Software type		Unity Pro Large version 3.0			
License type version 3.0		Single (1 workstation)	Group (3 workstations)	Team (10 workstations)	Site (> 10 workstations)
References	Software pack	UNYSPULFUCD30	UNYSPULFGCD30	UNYSPULFTCD30	UNYSPULFFCD30
	Update (3)	UNYSPULZUCD30	UNYSPULZGCD30	UNYSPULZTCD30	UNYSPULZFC30
Software type		Unity Pro Extra Large version 3.0			
License type version 3.0		Single (1 workstation)	Group (3 workstations)	Team (10 workstations)	Site (> 10 workstations)
References	Software pack	UNYSPUEFUCD30	UNYSPUEFGCD30	UNYSPUEFTCD30	UNYSPUEFFCD30
	Update (4)	UNYSPUEZUCD30	UNYSPUEZGCD30	UNYSPUEZTCD30	UNYSPUEZFC30

- (1) From Concept S, PL7 Micro, ProWORX NxT Lite and ProWORX 32 Lite
 (2) From Concept S/M, PL7 M/J, ProWORX NxT Lite and ProWORX 32 Lite
 (3) From Concept S /M, PL7 M/J/P, ProWORX NxT Lite and ProWORX 32 Lite
 (4) From all models Concept, PL7, ProWORX NxT and ProWORX 32

Unity Pro is common programming software for debugging and operation of Modicon M340, Premium, Quantum and Atrium programmable controller ranges. Unity Pro takes the recognized usage values of PL7 and Concept software and offers a complete set of new functions for improved productivity and opening to other software.

Five IEC61131-3 languages are supported as standard in Unity Pro with all debugging functions, either on the simulator or directly online with the programmable controller.

Thanks to symbolic variables independent of memory, structured data and user function blocks, application objects are a direct reflection of the automated process application components.


Unity Pro operator screens are user-configured in the application from graphic libraries. Operator accesses are simple and direct.

Unity V 3.0 integrates the PLCopen standard MFB (Motion Function Block) library, simplifying installation of motion controllers on CANopen machine buses: Altivar 31, Altivar 71, Lexium 05, Lexium 15 LP, MP and HP, IdA. Debugging and maintenance are simplified by animated graphic objects. For diagnostics, a window clearly and chronologically displays all system and application faults with timestamping at source.

The fault cause search navigation function enables precise location of the source of missing conditions.

XML format, the Web standard for data exchange, has been adopted as Unity application source format. By simple import/export, all or part of the application can be exchanged with other project software.

Finally, the converters integrated in Unity Pro automatically convert PL7 and Concept IEC 61131-3 standards and applications.



Unity software

Specialized software

Integrator system dedicated software

Software type		Unity Pro XL Alliance V3.0	
License type version 3.0		Single (1 workstation)	Team (10 workstations)
References	Software pack	UNYSPUEFUAL30	UNYSPUEFTAL30
	Old generation upgrade (1)	UNYSPUEZUAL30	UNYSPUSZTCD30
	Unity update	UNYSPUQZUAL30	UNYSPUQZTAL30
Software type		PLC Suite Alliance V3.0	
License type version 3.0		Single (1 workstation)	Team (10 workstations)
References	Pack (1)	UNYSPUQFUAL30	UNYSPUQFTAL30

(1) Including Unity Pro XL Alliance, Concept, PL7, ProWORX



Unity Pro application comparison software

Software type		Unity Dif
License type version 2.0		Single (1 workstation), French and English languages (software and documentation)
Reference	Software extension (1)	UNY SDU DFU CD20

(1) Requires version Unity Pro XL >/ V2.1



PLC application and Modicon M340 embedded software update

Software type		Unity Loader
License type version 1.0		Single (1 workstation)
Reference	Software pack (1)	UNY SMU ZUCD10

(1) This software is also included in all Unity Pro software packs



SFC View application diagnostic and monitoring software

Software type		Unity SFC View		
License type version 2.0		Single (1 workstation)	Team (10 workstations)	Site (> 10 workstations)
References	Software pack	UNYSDUMFUCD20	UNYSDUMFTCD20	UNYSDUMFFCD20



EF/EFB function development software in C language

Software type		Unity EFB Toolkit
License type version 3.0		Single (1 workstation), English language (software and documentation)
References	Software pack	UNYSPUFUCD30E
	Renewal	UNYCSPSPUZBU



Batch/process application design and generation software


Software type		Unity UAG (Unity Application Generator)		
License type version 2.3		Single (1 workstation)	Team (> 10 workstations)	Site (> 10 workstations)
References	Software pack	UAGSEWLFUCD23	UAGSEWLYTCD23 (1)	UAGSEWLFFCD23

(1) Also includes Unity Pro XL Group (3 workstations) and Concept XL Group (3 workstations)



Specific Unity Pro solution design software pack

Software type		Unity UDE (Unity Developer's Edition)
License type		Single (1 workstation), English language (software and documentation)
Reference	Software pack	UNYUDEVFUCD21E



PL7 is the common programming, debugging and operating software for the TSX Micro and Premium ranges of PLCs as well as Atrium coprocessors (see pages 3/12, 3/18 and 3/26).

PL7 offers 4 IEC languages: Instruction List (IL), Ladder Diagram (LD), Structured Text (ST) and Sequential Function Chart (SFC). You can use the most suitable language for each function in your application, making use of the multi-tasking structure of the processors.

For using application-specific functions, PL7 directly integrates the application-specific screens required for configuration and adjustment as well as supervisory and diagnostics activities.

Type of software		PL7 Micro for TSX Micro platform			
Type of license version 4.5		Single (1 station)	Single with SyCon V2.8	Group (3 stations)	Open Team (10 stations)
Reference	Software package	TLXCDPL7MP45	TLXCDPL7MPC45	TLXCD3PL7MP45	TLXOTPL7MP45M
	Update (1)	TLXRCDDL7MP45M	TLXRCDDL7MPC45M	TLXRCDD3PL7MP45M	–
PL7 Junior for TSX Micro/Premium and Atrium coprocessor platforms					
Type of license version 4.5		Single (1 station)	Group (3 stations)		
Reference	Software package	TLXCDPL7JP45	TLXCD3PL7JP45		
	Update (1)	TLXRCDDL7JP45M	TLXRCDD3PL7JP45M		
	Upgrade (2)	TLXUCDDL7JP45M	TLXUCDD3PL7JP45M		
PL7 Pro for TSX Micro/Premium and Atrium coprocessor platforms					
Type of license version 4.5		Single (1 station)	Group (3 stations)	Open Team (10 stations)	Open Site
Reference	Software package	TLXCDPL7PP45	TLXCD3PL7PP45	TLXOTPL7PP45M	TLXOSPL7PP45M
	Update (1)	TLXRCDDL7PP45M	TLXRCDD3PL7PP45M	–	–
	Upgrade (2)	TLXUCDDL7PP45M	TLXUCDD3PL7PP45M	–	–

(1) From the previous software version.

(2) From lower level, earlier version software.

Specialist tools

EF function development software in C language

Type of software		PL7 SDKC for EF function development software in C language
PL7 SDKC software extension		For PL7 Micro/Junior/Pro
Reference		TLXLSKDCPL741M

Development of applications in C language

Type of software		PL7 FUZ for processing process applications using fuzzy logic
PL7 FUZ software extension		For PL7 Micro/Junior/Pro, TSX Micro/Premium
Reference		TLXLPL7FUZ34M

Comparison of PL7 applications


Type of software		PL7 DIF for comparison of applications
PL7 DIF software extension		For PL7 Pro, TSX Micro/Premium
Type of license		Single (1 station) Site (> 10 stations)
Reference		TLXCDPL7DIF42 TLXOSPL7DIF42

Availability of control systems based on Premium platforms

Type of software		Warm Standby redundant
Warm Standby software extension		For PL7 Junior/Pro
Type of license		Single (1 station)
Reference		TLXCDWSBYP40F / E

Programming software

For Modicon Quantum, Momentum



Concept is the IEC programming software for the Momentum and Quantum range of PLCs. It provides advanced Microsoft Windows based tools that deliver a multi-language development environment for control system programming.

Uses familiar, standardized editors, bundled in a single application to create and integrate PLC control, communication and diagnostic logic.

Five IEC editors give users the freedom to choose the programming language that fits their application requirements: Function Block Diagram (FBD), Ladder Diagram (LD), Sequential Function Chart (SFC), Structured Text (ST) and Instruction List (IL).

Type of software		Concept for Quantum/Momentum platforms			
Type of license version 2.6		Single (1 station)	Group (3 stations)	10 users (10 stations)	Site
Software references	Concept S	372SPU47101V26	–	–	–
	Concept M	372SPU47201V26	–	–	–
	Concept XL	372SPU47401V26	372SPU47411V26	372SPU47421V26	372SPU47431V26
Update references	Concept S (3)	372ESS47101	–	–	–
	Concept M (3)	372ESS47201	–	–	–
	Concept XL (3)	372ESS47401	372ESS47403	372ISS4740310	372ISS4741000

(3) From an earlier software version.

Specialist tools

EF/EFB function development software in C language

Type of software		Concept EFB Toolkit	
Type of license		Version 2.6	Upgrade version 2.6
Reference	Software package	332SPU47001V26	372ESS47001

Concept service version limited to application loading

Type of software		Concept Application Loader
Type of license		Version 2.6
Reference	Software package	372SPU47701V26

Software for designing and generating batch/process applications

Type of software		Unity UAG (Unity Application Generator)	
Type of license version 3.0		Single (1 station)	Site
Reference	Medium Software package	UAGSEWMFUCD22	UAGSEWMFFCD22
	Large Software package	UAGSEWLFUCD22	UAGSEWLFFCD22

SFC View application diagnostic and monitoring software

Type of software		Concept SFC View		
Type of license version 3.0		Single (1 station)	Group (10 stations)	Site (100 stations)
Reference		372SFV16000V30	372SFV16020V30	372SFV16030V30

ProWORX for Modicon Quantum, Momentum

ProWORX 32 is the flexible, easy-to-use cross-platform LL984-programming software for Modicon range PLCs. It gives you the power to program your Modicon controllers online or offline, manage your I/O subsystems, and analyze your plant's activity in real-time, all in a familiar Windows environment.

ProWORX 32 provides client/server capabilities to organize user-groups and -rights, store projects at a central location and realize office-plant floor bridging.

The project emulator provides the ability to test projects prior to running them in the PLC run-time environment to ensure your system will run at peak efficiency.



Type of software		ProWORX for Quantum/Momentum platforms			
Type of license version 2.1		Single (1 station)	Group (3 stations)	Multi-user (10 stations)	Site
Software references	ProWORX 32 Server	372SPU78001PSEV	–	–	–
	ProWORX 32 Suite	372SPU78001PSSV	–	–	–
	ProWORX 32 Client, Full Dev.	372SPU78001PDEV	372SPU78001PSTH	372SPU78001PSTE	372SPU78001SITE
	ProWORX 32 Online	372SPU78101PONL	–	–	–
	ProWORX 32 Lite	372SPU71001PLDV	372SPU71001PLTH	372SPU71001PLTE	–
Upgrade to ProWORX 32references (4)		372SPU78401LPUP	372SPU78401LPSTH	372SPU78401LPTE	–

(4) Only possible for customers, who are "up-to-date" with CSP (continuing support program)

Schneider Electric Industries SAS

Head office
89, bd Franklin Roosevelt
92506 Rueil-Malmaison Cedex
France

www.schneider-electric.com

Owing to changes in standards and equipment, the characteristics given in the text and images in this document are not binding until they have been confirmed with us.

Design: IGS-CP

Photos: Schneider Electric - Image bank

Print: Ingoprint